



- NOTES
- One example of the rotation of Ref. No. ⑤ to Ref. No. ① is shown.
 - The recommended torque of Ref. No. ⑤ : 2 TO 3 N·m.
 - Across flats hexagon head of Ref. No. :1.27 the recommended clamp torque of Ref. No. ⑧ : 0.3 to 0.4 N·m.
 - The cable pull and twisting strength and other characteristics may differ, depending on the cable structure. Please confirm before the use.
 - LOCTITE 243 HENKEL JAPAN or equivalent is recommended to prevent Ref. No. ①, ⑦ and ⑧ for loosening.

4	DIALYL PHTHALATE	(BLACK)	UL94V-0	8	STEEL	NICKEL PLATING	HEXAGON SOCKET SET SCREW M2. 6X0.45X2
3	DIALYL PHTHALATE	(BLACK)	UL94V-0	7	BRASS	NICKEL PLATING	JIS B 1101 M2X0.4X8
2	COPPER ALLOY	SILVER PLATING	2 μm min.	6	ZINC ALLOY	MATTE FINISH NICKEL PLATED	
1	ZINC ALLOY	MATTE FINISH NICKEL PLATED		5	ZINC ALLOY	MATTE FINISH NICKEL PLATED	
NO.	MATERIAL	FINISH	REMARKS	NO.	MATERIAL	FINISH	REMARKS
UNITS mm		SCALE 2 : 1	COUNT △	DESCRIPTION OF REVISIONS		DESIGNED	CHECKED
DATE		APPROVED : HY. KOBAYASHI 15.10.27		DRAWING NO. EDC-027936-00-00			
CHECKED : HY. KOBAYASHI 15.10.27		DESIGNED : HT. ZENBA 15.10.26		PART NO. RM12BJB-4PH			
DRAWN : HT. ZENBA 15.10.26		CODE NO. CL109-0831-6-00		△ 1/1			