

Coaxial Cable Connector 21_PC35-50-2-5/199_U

Description

Straight cable jack

Interface standards

IEC 60169-23

Technical Data

Electrical Data

Impedance	50 Ω		
Interface frequency max.	26.5 GHz		
Frequency range	DC to 10 GHz	10 to 18 GHz	18 to 26.5 GHz
Return loss	27 dB	28 dB	22 dB

Mechanical Data

Centre contact	plugged
Outer contact	soldered

Environmental Data

Operating temperature	-60 °C to 100 °C
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (without Nickel underplating)
Outer contact	Stainless Steel	
Body	Stainless Steel	
Insulator	PS (Polystyrene)	

Related Documents

Outline drawing	DOU-00193442
Catalogue drawing	DCA-00220921
Assembly instruction	DOC-0000381865

Ordering Information

Single package	21_PC35-50-2-5/199_UE
----------------	-----------------------

Additional Information

Suitable cables	MULTIFLEX_86
-----------------	--------------

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

HUBER+SUHNER:

[21_PC35-50-2-5/199_UE](#)