



THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF AMPHENOL CABLES ON DEMAND. ANY REPRODUCTION OR DISCLOSURE TO THIRD PARTIES, IN PART OR WHOLE, WITHOUT THE EXPRESS WRITTEN PERMISSION OF AMPHENOL CABLES ON DEMAND IS PROHIBITED.

REVISIONS			
REV.	DESCRIPTION	DATE	APPROVED
A	NEW RELEASE	2/APR/2014	



LENGTH




CAT.6A FTP LAN CABLE:

1. Conductor (Stranded): 26AWG (7X0.16mm);
2. Insulation: HD-PE;
3. Color Code:
PAIR 1: Blue & White/Blue
PAIR 2: Orange & White/Orange
PAIR 3: Green & White/Green
PAIR 4: Brown & White/Brown
4. Al/Mylar: Coverage 100%; Overlap 25%/min;
5. Drain: 7/0.16±0.01mm Tinned Copper;
6. Cable Marking:

Amphenol Cables on Demand TYPE CM 26AWG 4PR 75° C
(UL) c(UL) E314104 TIA/EIA-568-B-2-10 FTP CAT.6A

7. Rated Temperature: 75° C.
8. Rated Voltage: 300V.
9. UL cUL CM TYPE.
10. Impedance: 100±15% Ω (1~500 MHz)
11. DC-Resistance Capacitance Unbalance: 5 %
12. DC-Resistance: 14.8Ω/100m AT 20° C MAX
13. Bandwidth: 500 Mhz
14. Bending Radius: 25.4mm (1") min
15. Transmission Requirements TIA/EIA-568-B-2-10 PATCH CORD

Length Tolerance:
Length ≤ 0.5M +30/-0mm
Length > 0.5M & < 1M +50/-0mm
Length ≥ 1M & ≤ 5M +/-50mm
Length > 5M & < 10M +/-100mm



PIN OUT: T568B		
PLUG 1	PLUG 2	COLOR
PIN 1	PIN 1	WHITE/ORANGE
PIN 2	PIN 2	ORANGE
PIN 3	PIN 3	WHITE/GREEN
PIN 4	PIN 4	BLUE
PIN 5	PIN 5	WHITE/BLUE
PIN 6	PIN 6	GREEN
PIN 7	PIN 7	WHITE/BROWN
PIN 8	PIN 8	BROWN
Shielded	Shielded	DRAIN WIRE



UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES			
DECIMALS	ANGLES	E&R NO.	
X	±X	APPROVALS	DATE
.XX	±.XX	LF	2/APR/2014
.XXX	±.XXX	CHECKED	BA
		RESP ENG	
		MFG ENG	
THIRD ANGLE PROJECTION			
Amphenol Cables on Demand 20 VALLEY ST. ENDICOTT, NY 13760			
ASM CBL RJ45/RJ45 FTP CAT.6A			
SIZE	DWG. NO.	REV.	
A	MP - 6ARJ45SNNX	A0	

NOTES: UNLESS OTHERWISE SPECIFIED