Mallory Sonalert Products, Inc.				Part #: JT120-RYG-CDL			
Sales Outline Drawing				Revision:		С	
Specifications:							
Stack Number:	1	2	3				
LED Color:	RED	YELLOW	GREEN				
Connection Wires:	Red and Brown	Yellow and Brown	Green and Brown				
LED Current Draw:	<210 mA	<230 mA	<190 mA				
Rated Voltage:		•	120 VAC	C			
Operating Voltage:	90-120 VAC						
Sound Level Category:	Loud	Loud	Loud	Loud			
Mode of Operation:	Continuous	Medium Pulse (5PPS)	Double Pulse (0.	5PPS)	Continuous	for 5 sec then 0.1s beep until reset	
Connection:	Black and Gray Wires	Black and Gray Wires; Orange wire connected to	Black and Gray Wir wire connected to Gr wire			ray wires; Orange and Purple nected to Green/Yellow wire	
Sound Current Draw:	40mA Max.	40mA Max.	40mA Max	40mA Max.		40mA Max.	
Loudness @ 1m:	80-85 dB(A) Typ.						
Frequency:	2000 ± 500 Hz						
Total Max Current:	<670mA with all LED's and sound unit working						
Operating Temperature:	-25° ~ +60°C						
Lens Color:	Opaque White						
Material:	ABS FR15U						
Mounting Method:	Direct Mount using 1/2" NPT Stainless Steel Pipe and Nut						
Weight Typical (g):	365						
NEMA 12:	Approved						
Options:	Please contact factory.						
Dimonejone: Jaches /m	``	cIII Pecoar		-		POUS Complian	

**Dimensions:** Inches (mm)

TOP VIEW

## **cUL** Recognized

MOUNTING DIAGRAM ROHS Compliant

PATENT NUMBER 10309594

6.7 [169.8]

GREEN

7.4 [188.9]

Ø0.88 [Ø22.2]

KNDCK DUT

FOR WIRES

2.7 [68.3]

LED OPERATION: CONNECT STACK COLOR WIRE TO POWER AND BROWN WIRE TO POWER.

SOUND OPERATION: CONNECT GRAY AND BLACK WIRES TO POWER FOR CONTINUOUS SOUND.

FOR MEDIUM PULSE, CONNECT GRAY & BLACK TO POWER AND ORANGE WIRE TO GREEN/YELLOW WIRE. FOR DOUBLE PULSE, CONNECT GRAY & BLACK TO POWER AND PURPLE WIRE TO GREEN/YELLOW WIRE. FOR CONT/BEEP, CONNECT GRAY & BLACK TO POWER AND ORANGE & PURPLE TO GREEN/YELLOW WIRE.