

# HSL-TB32-MD

## 32-CH Separate I/O Terminal Base



### Specifications

■ General Description	Separate I/O wiring connection for HSL I/O modules
	Every I/O points uses 3-pin connector
	Pin definition is signal/ground/power (from left to right)
	Separate fuse protection for each I/O points
	(jumper selection)
	Supports common/separate DC power supply
	(jumper selection)
	Terminator resistor on board (jumper selection)
	Interlocking design for rugged installation
	Power LED indicator


■ I/O Wire Gauge	20 AWG. (max.); 28 AWG. (min.)
■ Power Supply	22 V to 26 V <sub>DC</sub>
■ Dimensions	129 x 107 x 47.5 mm (W x L x H)

### Support Modules

- HSL-DI16DO16-M-NN
- HSL-DI32-M-N
- HSL-DO32-M-N

# HSL-TB32-M-DIN

## 32-CH I/O Terminal Base



### Specifications

■ General Description	Field I/O wiring connection for HSL I/O modules
	Spring terminal for easy field wiring
	Power and ground included for each signal channel
	Interlocking design for rugged installation
	Power LED indicator
	DIN rail mounting
	Terminator resistor on board


■ I/O Wire Gauge	20 AWG. (max.); 28 AWG. (min.)
■ Power supply	22 V to 26 V <sub>DC</sub>
■ Dimensions	128.5 x 85.5 x 108 mm (W x L x H)

### Support Modules

- HSL-DI16DO16-M-NN
- HSL-DI32-M-N
- HSL-DO32-M-N
- HSL-R8DI16-M-N
- HSL-AI16AO2-M-VV-AV

# HSL-TB32-U-DIN

## 32 Points Universal Terminal Base



### Specifications

■ General Description	Field I/O wiring connection for HSL I/O modules
	Spring terminal for easy field wiring
	Power and ground included for each signal channel
	Interlocking design for rugged installation
	Power LED indicator
	DIN rail mounting
	Terminator resistor on board

■ I/O Wire Gauge	20 AWG. (max.); 28 AWG. (min.)
■ Power Supply	22 V to 26 V <sub>DC</sub>
■ Dimensions	126 x 120.1 x 107.3 mm (W x L x H)

### Support Modules

- HSL-DI16DO16-DB-NN
- HSL-DI32-DB-N
- HSL-DO32-DB-N

# HSL-TB64

## 64 Points High Density Terminal Base



### Specifications

■ General Description	Field I/O wiring connection for HSL I/O modules
	Spring terminal for easy field wiring
	Power and ground included for each signal channel
	Interlocking design for rugged installation
	Power LED indicator
	DIN rail mounting
	Terminator resistor on board

■ I/O Wire Gauge	20 AWG. (max.); 28 AWG. (min.)
■ Power Supply	22 V to 26 V <sub>DC</sub>
■ Dimensions	168.7 x 120.1 x 107.1 mm (W x L x H)

### Support Modules

- HSL-DI16DO16-DB-NN
- HSL-DI32-DB-N
- HSL-DO32-DB-N