

# HSL-TB32-MD

## 32-CH Separate I/O Terminal Base



### Specifications

|                       |  |
|-----------------------|--|
| ■ General Description | Separate I/O wiring connection for HSL I/O modules<br>Every I/O points uses 3-pin connector<br>Pin definition is signal/ground/power (from left to right)<br>Separate fuse protection for each I/O points (jumper selection)<br>Supports common/separate DC power supply (jumper selection)<br>Terminator resistor on board (jumper selection)<br>Interlocking design for rugged installation<br>Power LED indicator<br>DIN rail mounting<br>Power and ground included for each signal channel |
|-----------------------|--|


|                  |                                 |
|------------------|---------------------------------|
| ■ I/O Wire Gauge | 20 AWG. (max.); 28 AWG. (min.)  |
| ■ Power Supply   | 22 V to 26 V <sub>DC</sub>      |
| ■ Dimensions     | 129 x 107 x 47.5 mm (W x L x H) |

### Support Modules

- HSL-DI16DO16-M-NN
- HSL-DI32-M-N
- HSL-DO32-M-N

# HSL-TB32-M-DIN

## 32-CH I/O Terminal Base



### Specifications

|                       |  |
|-----------------------|--|
| ■ General Description | Field I/O wiring connection for HSL I/O modules<br>Spring terminal for easy field wiring<br>Power and ground included for each signal channel<br>Interlocking design for rugged installation<br>Power LED indicator<br>DIN rail mounting<br>Terminator resistor on board |
| ■ I/O Wire Gauge      | 20 AWG. (max.); 28 AWG. (min.)   |
| ■ Power supply        | 22 V to 26 V <sub>DC</sub>   |
| ■ Dimensions          | 128.5 x 85.5 x 108 mm (W x L x H)  |

### Support Modules

- HSL-DI16DO16-M-NN
- HSL-DI32-M-N
- HSL-DO32-M-N
- HSL-R8DI16-M-N
- HSL-AI16AO2-M-VV-AV

# HSL-TB32-U-DIN

## 32 Points Universal Terminal Base



### Specifications

|                       |  |
|-----------------------|--|
| ■ General Description | Field I/O wiring connection for HSL I/O modules<br>Spring terminal for easy field wiring<br>Power and ground included for each signal channel<br>Interlocking design for rugged installation<br>Power LED indicator<br>DIN rail mounting<br>Terminator resistor on board |
| ■ I/O Wire Gauge      | 20 AWG. (max.); 28 AWG. (min.)   |
| ■ Power Supply        | 22 V to 26 V <sub>DC</sub>   |
| ■ Dimensions          | 126 x 120.1 x 107.3 mm (W x L x H)   |

### Support Modules

- HSL-DI16DO16-DB-NN
- HSL-DI32-DB-N
- HSL-DO32-DB-N

# HSL-TB64

## 64 Points High Density Terminal Base



### Specifications

|                       |  |
|-----------------------|--|
| ■ General Description | Field I/O wiring connection for HSL I/O modules<br>Spring terminal for easy field wiring<br>Power and ground included for each signal channel<br>Interlocking design for rugged installation<br>Power LED indicator<br>DIN rail mounting<br>Terminator resistor on board |
| ■ I/O Wire Gauge      | 20 AWG. (max.); 28 AWG. (min.)   |
| ■ Power Supply        | 22 V to 26 V <sub>DC</sub>   |
| ■ Dimensions          | 168.7 x 120.1 x 107.1 mm (W x L x H)   |

### Support Modules

- HSL-DI16DO16-DB-NN
- HSL-DI32-DB-N
- HSL-DO32-DB-N