


REV. 0  
DCO 142639

COIL: @ 25°C  
 RESISTANCE \_\_\_\_\_ 1560 OHMS ± 10%  
 NOMINAL VOLTAGE \_\_\_\_\_ 26.5 VDC  
 MUST OPERATE \_\_\_\_\_ 14.2 VDC  
 \_\_\_\_\_  
 MUST RELEASE \_\_\_\_\_ 8.0 VDC MAX, 1.37 VDC MIN.

ENVIRONMENT:  
 VIBRATION \_\_\_\_\_ 10 \_\_\_\_\_ CPS TO \_\_\_\_\_ 3000 \_\_\_\_\_ CPS @ \_\_\_\_\_ 30 \_\_\_\_\_ g's  
 SHOCK \_\_\_\_\_ 75 \_\_\_\_\_ g's \_\_\_\_\_ 6 \_\_\_\_\_ MS. DURATION  
 TEMPERATURE \_\_\_\_\_ -65 \_\_\_\_\_ °C TO \_\_\_\_\_ +125 \_\_\_\_\_ °C

NOTES: \_\_\_\_\_ OPERATE TIME 2 MS MAX  
 \_\_\_\_\_ RELEASE TIME 1.5 MS MAX  
 \_\_\_\_\_ CONTACT STABILIZATION 2.0 MS MAX.

CUSTOMER DATA SHEET



TERMINAL VIEW

CONTACT RATING: LOW LEVEL TO  
 1A 28 VDC RESISTIVE 100,000  
 OPERATIONS

DR. PBB 1/18/01

CK. *[Signature]*

**CI Technologies**  
 advanced control electronic solutions

CUST. \_\_\_\_\_ QPL  
 CUST. NO. M39016/9-104P REV. \_\_\_\_\_

JMA RELAY

JMACG-26XPS