LEOPARD IMAGING INC

Rev 1.1

LI-TX1-KIT-IMX185CS Data Sheet

Key Features

- Compatible with Nvidia Jetson TX1
- MIPI interface
- Support up to three IMX185 cameras
- Sony Diagonal 8.58mm Type 1/1.9 CMOS Image Sensor IMX185LQJ
- Active pixels: 1937H x 1217V
- Length of the I-PEX cable: 300mm
- Support CS lens
- Provide customization services
- Weight: 78 g
- Part#: LI-TX1-KIT-IMX185CS

BOM

#	Items	QTY
1	LI-JTX1-MIPI-ADPT	1
2	LI-IMX185-MIPI-CS	1
3	FAW-1233-03 cable	1

Lens Spec

- Model: ES0522F.IR
- Focal length: 5.0 mm
- Aperture, F/#: 2.2
- Built in 650nm IR cut filter
- FOV (D/H/V): 102° / 90° /50°
- TV Distortion: < -8%
- Mount Type: CS

Dimensions (LI-JTX1-MIPI-ADPT)



Leopard Imaging Inc.

1130 Cadillac Ct., Milpitas, CA 95035,USA
Phone: +1-408-263-0988
Fax: +1-408-217-1960
Email:sales@leopardimaging.com
Website: www.leopardimaging.com
www.leopard-security.com

Dimensions (LI-IMX185-MIPI-CS)



Dimensions (FAW-1233-03)



Work on Nvidia Jetson TX1

Leopard Imaging Inc.

1130 Cadillac Ct., Milpitas, CA 95035,USA
Phone: +1-408-263-0988
Fax: +1-408-217-1960
Email:sales@leopardimaging.com
Website: www.leopardimaging.com
www.leopard-security.com

LI-JTX1-MIPI-ADPT



Interfaces

Interface J1

- Part#: 20525-030E-02C
- Number of Positions: 30
- Pitch: 0.4mm
- Mating I-PEX cable: FAW-1233-03 (300mm)



Interface J2

- Part#: 20525-030E-02C
- Number of Positions: 30
- Pitch: 0.4mm
- Mating I-PEX cable: FAW-1233-03 (300mm)



Interface J3

- Part#: 20525-030E-02C
- Number of Positions: 30
- Pitch: 0.4mm
- Mating I-PEX cable: FAW-1233-03 (300mm)



Leopard Imaging Inc.

1130 Cadillac Ct., Milpitas, CA 95035,USA
Phone: +1-408-263-0988
Fax: +1-408-217-1960
Email:sales@leopardimaging.com
Website: www.leopardimaging.com
www.leopard-security.com

Interface J10

- Part#: QTH-060-01-L-D-A
- Number of Positions: 120
- Number of Rows: 2
- Pitch: 0.5 mm



Leopard Imaging Inc.

1130 Cadillac Ct., Milpitas, CA 95035,USA
Phone: +1-408-263-0988
Fax: +1-408-217-1960
Email:sales@leopardimaging.com
Website: www.leopardimaging.com
www.leopard-security.com

LI-IMX185-MIPI-CS



Camera Spec	
Image Sensor	Sony Diagonal 8.58 mm (Type 1/1.9) Solid-state Image Sensor IMX185
Optical format	1/1.9”
Number of active pixels	1952 (H) x 1243 (V)
Pixel size	3.75um (H) x 3.75um (V)
Color or Mono	Color
Interface	MIPI interface
Lens mount	CS
IR switcher	Support
Weight	58 g
Interfaces	
Interface J2: ▪ Part#: 20525-030E-02C ▪ Number of Positions: 30 ▪ Pitch: 0.4mm ▪ Mating I-PEX cable: FAW-1233-03 (300mm)	
Interface J3: ▪ Part#: 1734829-2 ▪ Number of Positions: 2 ▪ Pitch: 1.25mm	
Interface J5: ▪ Part#: 1734829-2 ▪ Number of Positions: 2 ▪ Pitch: 1.25mm	

Leopard Imaging Inc.

1130 Cadillac Ct., Milpitas, CA 95035,USA
Phone: +1-408-263-0988
Fax: +1-408-217-1960
Email:sales@leopardimaging.com
Website: www.leopardimaging.com
www.leopard-security.com

Absolute Maximum Ratings

Item	Symbol	Min.	Max.	Unit	Remarks
Supply voltage (analog 3.3 V)	AV_{DD}	-0.3	4.0	V	
Supply voltage (digital 1.8 V)	OV_{DD}	-0.3	3.3	V	
Supply voltage (digital 1.2 V)	DV_{DD}	-0.3	2.0	V	
Input voltage	VI	-0.3	OV_{DD} + 0.3	V	Not exceed 3.3 V
Output voltage	VO	-0.3	OV_{DD} + 0.3	V	Not exceed 3.3 V
Guaranteed operating temperature	Topr	-30	+75	˚C	
Storage guarantee temperature	Tstg	-40	+80	˚C	
Performance guarantee temperature	Tspec	-10	+60	˚C	

Recommended Operating Conditions

Item	Symbol	Min.	Typ.	Max.	Unit
Supply voltage (analog 3.3 V)	AV_{DD}	3.15	3.3	3.45	V
Supply voltage (digital 1.8 V)	OV_{DD}	1.7	1.8	1.9	V
Supply voltage (digital 1.2 V)	DV_{DD}	1.1	1.2	1.3	V

Spectral Sensitivity Characteristics



1130 Cadillac Ct., Milpitas, CA 95035,USA
Phone: +1-408-263-0988
Fax: +1-408-217-1960
Email:sales@leopardimaging.com
Website: www.leopardimaging.com
www.leopard-security.com

DC Characteristics

Item		Pins	Symbol	Conditions	Min.	Typ.	Max.	Unit
Supply voltage	Analog	$V_{DD}Hx$	AV_{DD}		3.15	3.30	3.45	V
	Digital	$V_{DD}Mx$	OV_{DD}		1.70	1.80	1.90	V
	Digital	$V_{DD}Lx$	DV_{DD}		1.10	1.20	1.30	V
Digital input voltage		XHS XVS XCLR INCK XMASTER OMODE SCK/SCL SDI/SDA XCE	VIH	XVS/XHS in slave mode	0.8 × OV_{DD}	—	—	V
			VIL		—	—	0.2 × OV_{DD}	V
Digital output voltage		DOP [11:0] DOM [11:0] DCKP DCKM	VCM	Low voltage LVDS	—	$OV_{DD}/2$	—	V
			VOD	Low voltage LVDS (Termination resistance100 Ω)	100	150	200	mV
		XHS XVS SDO	VOH	XVS/XHS in master mode	OV_{DD} -0.4	—	—	V
			VOL		—	—	0.4	V

Power Consumption

Item	Pins	Symbol	Typ.		Max.		Unit
			Standard luminous intensity	Saturated luminous intensity	Standard luminous intensity	Saturated luminous intensity	
Operating current CSI-2 serial output 4 Lane 12 bit, 60 frame/s 1080p-HD mode	$V_{DD}H$	IAV_{DD}	88	88	113	113	mA
	$V_{DD}M$	IOV_{DD}	2	2	4	4	mA
	$V_{DD}L$	IDV_{DD}	110	130	150	190	mA
Standby current	$V_{DD}H$	IAV_{DD}_STB	—		0.2		mA
	$V_{DD}M$	IOV_{DD}_STB	—		0.1		mA
	$V_{DD}L$	IDV_{DD}_STB	—		7.0		mA

Operating current:
(Typical value condition) : Supply voltage 3.3 V / 1.8 V / 1.2 V, Tj = 25 ˚C
(Maximum value condition) : Supply voltage 3.45 V / 1.9 V / 1.3 V, worst state of internal circuit operating current consumption, Tj = 60 ˚C
Standby (Maximum value condition) : Supply voltage 3.45 V / 1.9 V / 1.3 V, Tj = 60 ˚C, INCK = 0 V

Standard luminous intensity: luminous intensity at standard imaging condition I
Saturated luminous intensity: luminous intensity when the sensor is saturated.

Leopard Imaging Inc.

1130 Cadillac Ct., Milpitas, CA 95035,USA
Phone: +1-408-263-0988
Fax: +1-408-217-1960
Email:sales@leopardimaging.com
Website: www.leopardimaging.com
www.leopard-security.com

AC Specification

INCK



Duty Ratio = t_{WP} / t_P × 100

Item	Symbol	Min.	Typ.	Max.	Unit	Remarks
INCK clock frequency	f_{INCK}	f_{INCK} × 0.96	f_{INCK}	f_{INCK} × 1.02	MHz	f_{INCK} = 27 MHz, 54 MHz, 37.125 MHz, 74.25 MHz
INCK Low level width	t_{WLINCK}	4	—	—	ns	f_{INCK} = 27 MHz, 54 MHz, 37.125 MHz, 74.25 MHz
INCK High level width	t_{WHINCK}	4	—	—	ns	f_{INCK} = 27 MHz, 54 MHz, 37.125 MHz, 74.25 MHz
INCK clock duty	—	45.0	50.0	55.0	%	Define with 0.5 × OV_{DD}

*The INCK fluctuation affects the frame rate.

Leopard Imaging Inc.

XHS, XVS Input Characteristics In Slave Mode (XMASTER pin = High)



Item	Symbol	Min.	Typ.	Max.	Unit	Remarks
XHS Low level pulse width	t_{WLXHS}	4 / f_{INCK}	—	—	ns	
XHS High level pulse width	t_{WHXHS}	4 / f_{INCK}	—	—	ns	
XVS-XHS fall width	t_{HFDLY}	1 / f_{INCK}	—	—	ns	
XHS-XVS rise width	t_{VRDLY}	1 / f_{INCK}	—	—	ns	

1130 Cadillac Ct., Milpitas, CA 95035,USA
Phone: +1-408-263-0988
Fax: +1-408-217-1960
Email:sales@leopardimaging.com
Website: www.leopardimaging.com
www.leopard-security.com

I²C Communication



I²C Specification

Item	Symbol	Min.	Typ.	Max.	Unit	Remarks
Low level input voltage	V_{IL}	-0.3	—	0.3 × OV_{DD}	V	
High level input voltage	V_{IH}	0.7 × OV_{DD}	—	1.9	V	
Low level output voltage	V_{OL}	0	—	0.2 × OV_{DD}	V	OV_{DD} < 2 V, Sink 3 mA
High level output voltage	V_{OH}	0.8 × OV_{DD}	—	—	V	
Output fall time	tof	—	—	250	ns	Load 10 pF – 400 pF, 0.7 × OV_{DD} – 0.3 × OV_{DD}
Input current	Ii	-10	—	10	μA	0.1 × OV_{DD} – 0.9 × OV_{DD}
Capacitance for SCK (/SCL) , SDI (/SDA)	Ci	—	—	10	pF	

I²C AC Characteristics

Item	Symbol	Min.	Typ.	Max.	Unit
SCL clock frequency	f_{SCL}	0	—	400	kHz
Hold time (Start Condition)	t_{HDSTA}	0.6	—	—	μs
Low period of the SCL clock	t_{LOW}	1.3	—	—	μs
High period of the SCL clock	t_{HIGH}	0.6	—	—	μs
Set-up time (Repeated Start Condition)	t_{SUSTA}	0.6	—	—	μs
Data hold time	t_{HDDAT}	0	—	0.9	μs
Data set-up time	t_{SUDAT}	100	—	—	ns
Rise time of both SDA and SCL signals	t_R	—	—	300	ns
Fall time of both SDA and SCL signals	t_F	—	—	300	ns
Set-up time (Stop Condition)	t_{SUSTO}	0.6	—	—	μs
Bus free time between a Stop and Start Condition	t_{BUF}	1.3	—	—	μs

Leopard Imaging, Inc.

1130 Cadillac Ct., Milpitas, CA 95035,USA
Phone: +1-408-263-0988
Fax: +1-408-217-1960
Email:sales@leopardimaging.com
Website: www.leopardimaging.com
www.leopard-security.com

Power-on Sequence



Item	Symbol	Min.	Max.	Unit
1.2 V power supply rising → 1.8 V power supply rising	T_0	0	—	ns
1.8 V power supply rising → 3.3 V power supply rising	T_1	0	—	ns
Rising time of all power supply	T_2	—	200	ms
All power supply rising → External input time of INCK	T_3	0	—	ns
INCK active → Clear OFF	T_{LOW}	500	—	ns
Clear OFF Communication start	T_{XCE}	20	—	µs
Standby OFF (communication) → External input XHS, XVS (slave mode only)	T_{SYNC}	20	—	ms

Leopard Imaging, Inc.

1130 Cadillac Ct., Milpitas, CA 95035,USA
Phone: +1-408-263-0988
Fax: +1-408-217-1960
Email:sales@leopardimaging.com
Website: www.leopardimaging.com
www.leopard-security.com

Power-off Sequence



Item	Symbol	Min.	Max.	Unit
Standby ON (communication) → LP11 mode start	T_{STB}	Until FE		—
LP00 → XCLR falling (ULPSDIS = 0)	T_{CLR}	128	—	cycle
3.3 V power shut down → 1.8 V power shut down	T_4	0	—	ns
1.8 V power shut down → 1.2 V power shut down	T_5	0	—	ns
Shut down time of all power supply.	T_6	—	200	ms

Leopard Imaging, Inc.

1130 Cadillac Ct., Milpitas, CA 95035,USA
Phone: +1-408-263-0988
Fax: +1-408-217-1960
Email:sales@leopardimaging.com
Website: www.leopardimaging.com
www.leopard-security.com

Optical dimension

◆Image size (recommended recording pixels)

All-pixel scan	: diagonal 8.49mm (type 1/1.9)	
1080p-HD	: diagonal 8.26mm (type 1/1.9)	

◆Number of recommended recording pixels

All-pixel scan	: 1920 (H) × 1200 (V)	approx. 2.31 M pixels
1080p-HD	: 1920 (H) × 1080 (V)	approx. 2.07 M pixels

◆Unit cell size

3.75 μm（H) × 3.75 μm（V)

◆Recommended eye relief compensation distance : - 30mm to -∞

Inc

1130 Cadillac Ct., Milpitas, CA 95035,USA
Phone: +1-408-263-0988
Fax: +1-408-217-1960
Email:sales@leopardimaging.com
Website: www.leopardimaging.com
www.leopard-security.com