## xzcc12fdm40b



#### Main

Accessory / separate part category	Cabling accessories
Accessory / separate part type	Connector
Electrical connection	Straight female connector M12, 4 pins
Collar material	Metal
Status LED	Without
Cable connection	Screw terminal / wire size <= 0.75 mm² / clamping capacity 0.120.24 in (36 mm)

## Complementary

Cable gland type	Pg 7	
Cable connector fixing	Screw-on	
System Voltage	125 V AC 150 V DC	
Line Rated Current	3 A	
Enclosure material	Plastic	
Insulating resistance	> 1000 GΩ	
Contact resistance	<= 8000 μOhm	
Product weight	0.04 lb(US) (0.02 kg)	

#### **Environment**

IP degree of protection	IP67	9
ambient air temperature for operation	-40185 °F (-4085 °C)	1001


## Offer Sustainability

Not Green Premium product	Not Green Premium product
Compliant - since 0726 - Schneider Electric declaration of conformity	Compliant - since 0726 - Schneider Electric declaration of conformity
WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:
Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and	e Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and
Di-isodecyl phthalate (DIDP), which is known to the Stat of California to cause birth defects or other reproductive harm.	eDi-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm.
For more information go to www.p65warnings.ca.gov	For more information go to www.p65warnings.ca.gov

### Contractual warranty

Warranty period	18 months
-----------------	-----------

### **Dimensions**



# **Connections and Schemes**

