

## Half Slim

### SHE1B



#### GENERAL INFORMATION

TYPE	Half Slim	
INTERFACE	Serial ATA Revision 3.1	
DATA TRANSFER MODE	SATA 1.5Gbps, 3.0Gbps, 6.0Gbps	
CONNECTOR	15 + 7 pin Serial ATA	
OUTLINE DIMENSIONS	54 x 39 mm	
SERIES	SHE1B	
CONTROLLER TYPE	 TDK GBDriver GS1	
FLASH TYPE	SLC	pSLC/MLC
DENSITY RANGE	16 GB - 128 GB	pSLC: 16GB-256GB MLC: 32GB-512GB
DATA RETENTION	10 years @ life begin-10% 1 year @ life end	
ENDURANCE ENTERPRISE WL	100,000 P/E Cycles *Flash Block Level	pSLC: 20,000 P/E Cycles MLC: 3,000 P/E Cycles *Flash Block Level

#### TEMPERATURE

OPERATING TEMPERATURE	Commercial: 0°C to +70°C Industrial: -40°C to +85°C
STORAGE TEMPERATURE	Commercial: -25°C to +85°C Industrial: -40°C to +85°C

#### PERFORMANCE

Read (max.)	340 MByte/sec	pSLC: 400 MByte/sec MLC: 320 MByte/sec
Write (max.)	115 MByte/sec	pSLC: 165 MByte/sec MLC: 75 MByte/sec

#### ROBUSTNESS

MTBF	≥ 2,000,000 hours
SHOCK	1500G, 0.5ms
VIBRATION	20G, 10-2000Hz
HUMIDITY	0 to 90 % RH (No condensation)

#### ELECTRICAL DATA

VOLTAGE	5 V ± 10 %
POWER CONSUMPTION	<ul style="list-style-type: none"> <li>- Read: 250mA max.</li> <li>- Write: 270mA max.</li> <li>- Slumber: less than 100mA</li> </ul>

#### FEATURE LIST

FEATURES & TOOLS	<ul style="list-style-type: none"> <li>- In-House Designed Controller (HW/FW)               <ul style="list-style-type: none"> <li>- Power Fail Data Safety</li> <li>- Power Back-up Circuit</li> </ul> </li> <li>- Global static wear leveling               <ul style="list-style-type: none"> <li>- SMART</li> <li>- NCQ, TRIM</li> </ul> </li> <li>- AES 128/256bit encryption</li> </ul>
PART NUMBER	SHE1BxxxxTXDxB00SSA0