

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

**Part Number:** [0761701008](#)  
**Status:** **Active**  
**Overview:** [Impact™ Backplane Connector and Cable Assembly System](#)  
**Description:** [Impact™ 100 Ohm 3 Pair Right Angle Daughtercard Receptacle, Unguided, 8 Columns, 72 Circuits, Plated Through Hole Dimension 0.46mm, Lead-Free](#)

**Documents:**

|                                                              |                                                               |
|--------------------------------------------------------------|---------------------------------------------------------------|
| <a href="#">3D Model</a>                                     | <a href="#">Application Specification AS-76060-9999 (PDF)</a> |
| <a href="#">Drawing (PDF)</a>                                | <a href="#">Packaging Specification PK-70873-591 (PDF)</a>    |
| <a href="#">Product Specification PS-76060-999 (PDF)</a>     | <a href="#">Test Summary TS-76170-0001 (PDF)</a>              |
| <a href="#">Application Specification AS-76060-990 (PDF)</a> | <a href="#">RoHS Certificate of Compliance (PDF)</a>          |

**Agency Certification**

UL E29179

**General**

|                               |                                                                       |
|-------------------------------|-----------------------------------------------------------------------|
| Product Family                | Backplane Connectors                                                  |
| Series                        | <a href="#">76170</a>                                                 |
| Application                   | Conventional, Coplanar, Daughtercard                                  |
| Application Tooling Documents | TM-622018799                                                          |
| Component Type                | PCB Receptacle                                                        |
| Electrical Model              | Yes                                                                   |
| Overview                      | <a href="#">Impact™ Backplane Connector and Cable Assembly System</a> |
| Product Name                  | Impact™                                                               |
| UPC                           | 884982663138                                                          |

**Physical**

|                                |                                |
|--------------------------------|--------------------------------|
| Circuits (Loaded)              | 72                             |
| Circuits (maximum)             | 72                             |
| Color - Resin                  | Black                          |
| Durability (mating cycles max) | 200                            |
| First Mate / Last Break        | No                             |
| Flammability                   | 94V-0                          |
| Guide to Mating Part           | No                             |
| Keying to Mating Part          | None                           |
| Material - Metal               | High Performance Alloy (HPA)   |
| Material - Plating Mating      | Gold                           |
| Material - Plating Termination | Tin                            |
| Material - Resin               | High Temperature Thermoplastic |
| Net Weight                     | 0.001/g                        |
| Number of Columns              | 8                              |
| Number of Pairs                | 3                              |
| Number of Rows                 | 9                              |
| Orientation                    | Right Angle                    |
| PC Tail Length                 | 1.20mm                         |
| PCB Locator                    | No                             |
| PCB Retention                  | None                           |
| PCB Thickness - Recommended    | 1.00mm                         |
| Packaging Type                 | Tray                           |
| Pitch - Mating Interface       | 1.90mm                         |
| Pitch - Termination Interface  | 1.90mm                         |
| Plating min - Mating           | 0.762µm                        |
| Polarized to PCB               | No                             |
| Stackable                      | No                             |
| Temperature Range - Operating  | -55°C to +85°C                 |
| Termination Interface: Style   | Through Hole - Compliant Pin   |



Series image - Reference only

**EU ELV**

**Not Reviewed**

**EU RoHS**

**Not Reviewed**

**REACH SVHC**

Not Reviewed

**Halogen-Free**

**Status**

**Not Reviewed**

**Need more information on product environmental compliance?**

Email [productcompliance@molex.com](mailto:productcompliance@molex.com)  
Please visit the [Contact Us](#) section for any non-product compliance questions.

|            |              |
|------------|--------------|
| China ROHS | Not Reviewed |
| ELV        | Not Reviewed |

**Search Parts in this Series**

[76170](#) Series

**Mates With**

[76165](#) Impact™ 100 Ohm Vertical Header,  
[76410](#) Impact™ 100 Ohm Right Angle Header

**Use With**

[76153](#) Pirate Cannon Wide Guide Module

**Application Tooling | FAQ**

*Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.*

**Global**

| Description          | Product #                  |
|----------------------|----------------------------|
| Daughter Card        | <a href="#">0622018675</a> |
| Module Installation  |                            |
| Press-In Tool for 3- |                            |

**Electrical**

|                               |                 |
|-------------------------------|-----------------|
| Current - Maximum per Contact | 0.75A           |
| Data Rate                     | 25.0 Gbps       |
| Impedance                     | 100#            |
| Shield Type                   | N/A             |
| Shielded                      | No              |
| Voltage - Maximum             | 30V AC (RMS)/DC |

**Material Info**

**Reference - Drawing Numbers**

|                           |                             |
|---------------------------|-----------------------------|
| Application Specification | AS-76060-990, AS-76060-9999 |
| Electrical Model Document | EE-76170-003                |
| Packaging Specification   | PK-70873-591                |
| Product Specification     | PS-76060-999                |
| S-Parameter Model         | SP-76170-003                |
| Sales Drawing             | SD-76170-001                |
| Symbol/Footprint Data     | SYM-76170-1008              |
| Test Summary              | TS-76170-0001               |

|                             |                   |
|-----------------------------|-------------------|
| Pair by 8-Column Assemblies |                   |
| Impact Daughter             | <u>0622024300</u> |
| Card Extraction Tool        |                   |
| Impact™ Daughter            | <u>0622024600</u> |
| Card Module                 |                   |
| Removal Tool                |                   |

This document was generated on 06/10/2016

**PLEASE CHECK [WWW.MOLEX.COM](http://WWW.MOLEX.COM) FOR LATEST PART INFORMATION**