Between-Series Adapters

SMA to BMA

SMA Male Plug to BMA Female Jack


Model Number

ADT-2768-SM-BMF-02

SPECIFICATIONS

Frequency: DC - 18.0 GHz VSWR: 1.05 + .005 f (GHz) Impedance: 50 Ohms

Finish: Passivated Stainless Steel





SMA Bulkhead Female Jack to BMA Female Jack


Model Number

ADT-2805-SF-BMF-02

SPECIFICATIONS

Frequency: DC - 18.0 GHz VSWR: 1.05 + .005 f (GHz) Impedance: 50 Ohms

Finish: Passivated Stainless Steel





SMA Female Jack to BMA Female Jack - Bulkhead Mount


Model Number

ADT-2806-SF-BMF-02

SPECIFICATIONS

Frequency: DC - 18.0 GHz VSWR: 1.05 + .005 f (GHz) Impedance: 50 Ohms

Finish: Passivated Stainless Steel





SMA Male Plug to BMA Female Jack - Bulkhead Mount

Model Number

ADT-2807-SM-BMF-02

SPECIFICATIONS

Frequency: DC - 18.0 GHz VSWR: 1.05 + .005 f (GHz) Impedance: 50 Ohms

Finish: Passivated Stainless Steel

