
Product datasheet Characteristics

XUSZSC105R





Main

Range of product	Preventa Safety detection
Accessory / separate part category	Mounting and fixing accessories
Accessory / separate part type	Fixing column
Offer type	Without mirror
Product compatibility	XUSL.E16 to XUSL.E61 with 2 beams
Accessory / separate part destination	Safety light curtain type 2 Safety light curtain type 4

Complementary

Ambient air temperature for operation	14122 °F (-1050 °C) 14121 °F	
Ambient air temperature for storage	-13158 °F (-2570 °C) -13158 °F	
Kit composition	1 Pg 11 cable gland(s)	
Height	39.37 in (1000 mm)	
Height protected	24.02 in (610 mm)	
Product weight	8.16 lb(US) (3.7 kg)	

Environment

Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 1425 - Schneider Electric declaration of conformity	Compliant - since 1425 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Available	Available
WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:
Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and	e Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and
Di-isodecyl phthalate (DIDP), which is known to the StateDi-isodecyl phthalate (DIDP), which is known to the State of California to cause bir	


Di-isodecyl phthalate (DIDP), which is known to the StateDi-isodecyl phthalate (DIDP), which is known to the State of California to cause birth of California to cause birth defects or other reproductive defects or other reproductive harm. harm.

For more information go to www.p65warnings.ca.gov For more information go to www.p65warnings.ca.gov


Dimensions

With XUSZFB2





With XUSZFB1



Mounting and Clearance

