

WHITE-RODGERS DC PRODUCTS

Type 70 and 71 contactors

FEATURES

- High current capacity control
- Isolated or grounded coils
- Enclosed in dust-resistant case
- Longer steel encasement permits lower heat rise and more sensitive operation on Type 71

ENGINEERING DATA

Contacts

- Pole form— SPNO, SPDT
- Material— SPNO-copper or silver
SPDT-copper and silver or all silver
- Termination— $\frac{5}{16}$ "-24 UNF-2A thread

RATINGS					
Type	Volts DC	NO		NC	
		Cont.	Inrush	Cont.	Inrush
70	6	80A	300 A	60A	100 A
	12	80 A	150 A	60 A	60 A
	24 & 36	50 A	50 A	30 A	30 A
71	6	80A	300 A	60A	100 A
	12	80 A	150 A	60 A	60 A
	24 & 36	50 A	50 A	30 A	30 A

Coils

- Voltage—6 VDC through 36 VDC
- Termination—#10-32 UNF-2A thread
- Power (approximate)
 - Type 70 intermittent 23 watts
 - Type 70 continuous 9 watts
 - Type 71 intermittent 25 watts
 - Type 71 continuous 10 watts
- Connections
 1. Two coil terminals isolated from case
 2. One coil terminal with ground wire, one coil terminal isolated from case
 3. One coil lead common to NO terminal marked "BAT" (one terminal)
- Operate (77°F/25°C)
 - 75% of nominal coil voltage; 110% max. safe of nominal coil voltage



GENERAL DATA

Dielectric Strength

- 500 Volts

Temperature Range

- -40°F/-40°C to 122°F/50°C

Mechanical Life (no load)

- 250,000 operations

Electrical Life (rated load)

- 100,000 operations

Mounting Position

- Recommended mounting with cap down

Vibration

- 5 g's vertical and horizontal planes

Weight (approximate)

- Type 70—14.0 oz.
- Type 71—17.0 oz.

Duty Cycle

- Continuous
- Intermittent—10 seconds "on" maximum and minimum 60 seconds "off". One minute "on" maximum and minimum 6 minutes "off".

Hardware Torque Specification

- Contact Terminal: 45-55 inch-lbs.
- Coil Terminal: 12-18 inch-lbs.
- Mounting Bracket: 100 inch-lbs. max (a backup wrench must be used to hold the bottom nut stationary during installation)

COIL DATA					
TYPE 70			TYPE 71		
Volts DC	Resistance (Ohms)		Volts DC	Resistance (Ohms)	
	Int.	Cont.		Int.	Cont.
6	1.5	4.0	6	1.4	3.5
12	6.2	16.0	12	4.9	13.5
18	16.0	37.4	18	13.46	36.0
24	23.9	60.4	24	20.1	57.1
36	60.4	114.0	36	57.1	131.0

$$\underline{7x} - \underline{x} \quad \underline{xx} \quad \underline{xx} \quad \underline{xx} - \underline{x}$$