

NOTES:

1. MATERIALS AND FINISHES:
BNC STR CRIMP PLUG - PHOSPHOR BRONZE, NICKEL PLATING
CABLE - BELDEN 179DT



2. ELECTRICAL:
A. IMPEDANCE: 75 OHM

3. PACKAGING:
A. QUANTITY: SINGLE PACK
B. MARKING: BAG TO BE MARKED
"AMPHENOL RF, 115101-35-XX.XX AND DATE CODE".

THIRD ANGLE PROJ.

REVISIONS

REV	DESCRIPTION	DATE	ECO	APPR
A	RELEASE TO MFG.	07-Dec-16	2603	MR



LENGTH TABLE			
PART NUMBER (IMPERIAL)	PART NUMBER (METRIC)	LENGTH AND TOLERANCE 'L' IN INCHES [METERS]	LENGTH 'X' IN INCHES [METERS] MIN
115101-35-06.00	-	6.00 ± 0.25 [0.152 ± 0.006]	0.75 [0.019]
-	115101-35-M0.25	9.84 ± 0.25 [0.250 ± 0.006]	
115101-35-12.00	-	12.00 ± 0.25 [0.305 ± 0.006]	
115101-35-18.00	-	18.00 ± 0.25 [0.457 ± 0.006]	
-	115101-35-M0.50	19.69 ± 0.25 [0.500 ± 0.006]	1.50 [0.038]
115101-35-24.00	-	24.00 ± 0.50 [0.610 ± 0.013]	
-	115101-35-M0.75	29.53 ± 0.50 [0.750 ± 0.013]	
115101-35-30.00	-	30.00 ± 0.50 [0.762 ± 0.013]	
115101-35-36.00	-	36.00 ± 0.50 [0.914 ± 0.013]	
-	115101-35-M1.00	39.37 ± 0.50 [1.000 ± 0.013]	
115101-35-48.00	-	48.00 ± 0.50 [1.219 ± 0.013]	
115101-35-60.00	-	60.00 ± 1.50 [1.524 ± 0.038]	
-	115101-35-M2.00	78.74 ± 1.97 [2.000 ± 0.050]	
115101-35-90.00	-	90.00 ± 2.25 [2.286 ± 0.057]	
-	115101-35-M3.00	118.11 ± 2.95 [3.000 ± 0.075]	
115101-35-120	-	120.00 ± 3.00 [3.048 ± 0.076]	
-	115101-35-M4.00	157.48 ± 3.94 [4.000 ± 0.100]	
115101-35-180	-	180.00 ± 4.50 [4.572 ± 0.114]	
115101-35-300	-	300.00 ± 15.00 [7.620± 0.381]	

TOLERANCE TABLE	
LENGTH IN INCHES/FT [METERS]	TOLERANCE
0" - 23.90" [0 - 0.607]	±0.25" [0.006]
24.00" - 59.00" [0.610 - 1.499]	±0.50" [0.013]
5.0' - 24.9' [1.524 - 7.617]	±2.5%
25.0' & UP [7.620 & UP]	±5.0%

DESIGN REQUIREMENTS:

X FREQUENCY : DC TO 4 GHz

X CONTINUITY

VSWR : MAX.

X HI-POT : 300 VRMS

INS. LOSS : ____ dB MAX

OTHER

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES AND TOLERANCES ARE:		
2 PLACE DECIMAL	3 PLACE DECIMAL	ANGLES
±.015 (0,381 mm)	±.005 (0,127 mm)	± 1°

NOTICE - These drawings, specifications, or other data (1) are, and remain the property of Amphenol Corp. (2) must be returned upon request; and (3) are confidential and not to be disclosed to any person other than those to whom they are given by Amphenol Corp. the furnishing of these drawings, specifications, or other data by Amphenol Corp., or to any other person to anyone for any purpose is not to be regarded by implication or otherwise in any manner licensing, granting rights to permitting such holder or any other person to manufacture, use or sell any product, process or design, patented or otherwise, that may in any way be related to or disclosed by said drawings, specifications, or other data.

MATERIAL

SEE NOTES

DRAWN VIJIK	DATE 03-Oct-16
----------------	-------------------

DATE
03-Oct-16

ENGINEER VIJI K	DATE 03-Oct-16
--------------------	-------------------

DATE
03-Oct-16

REFERENCE EAR # 7288

APPROVED	DATE
K. CAPOZZI	07-Dec-16

DATE
07-Dec-16

CONFIGURATION LEVEL: In Work

CAD FILE

FINISH

TITLE _____

75 OHM BNC STR CRIMP PLUG
TO BNC STR CRIMP PLUG
USING BELDEN 179DT CABLE,
VARIOUS LENGTH

SCALE: 2.2:1.0	SHEET 2 OF 2
----------------	--------------

DWG SIZE
B

REV
A

Amphenol RF

www.amphenolrf.com

DRAWING NO. 115101-35-XX-XX

ITEM NO. 115101-35-XX-XX

PART NO. 115101-35-XX-XX