


## Semi-Precision Power Wirewound Resistor

### (N)AS Series

- 0.25 to 10 watts
- Tolerance down to  $\pm 0.5\%$
- 0.1 ohm to 150K ohms
- Resistance wire TCR  $\pm 20$  ppm/ $^{\circ}\text{C}$
- Non inductive (NAS) option
- Pb-free option is RoHS compliant




 All Pb-free parts comply with EU Directive 2011/65/EU amended by (EU) 2015/863 (RoHS3)

## Electrical Data

| Type      | Equivalent MIL-R-26 Style | Power Rating (watts)   |                       | AS Standard Range (ohms) |      | NAS Non-inductive Range (ohms) |      | Available Tolerance (%) |                   |
|-----------|---------------------------|------------------------|-----------------------|--------------------------|------|--------------------------------|------|-------------------------|-------------------|
|           |                           | 125 $^{\circ}\text{C}$ | 25 $^{\circ}\text{C}$ | Min.                     | Max. | Min.                           | Max. | <1R0                    | $\geq 1\text{R}0$ |
| (N)AS-1/4 | RW81                      | 0.25                   | 1                     | 0R2                      | 4K0  | 1R0                            | 500R | 3, 5                    | 0.5, 1, 3, 5      |
| (N)AS-1/2 |                           | 0.5                    | 1                     | 0R24                     | 6K0  | 1R0                            | 3K0  |                         |                   |
| (N)AS-1   | RW70U                     | 1                      | 2                     | 0R1                      | 7K5  | 0R1                            | 3K8  |                         |                   |
| (N)AS-1C  |                           | 1                      | 2                     | R05                      | 2K0  | 10R                            | 1K0  |                         |                   |
| (N)AS-2   | RW79U                     | 2                      | 3                     | 0R1                      | 20K  | 0R5                            | 10K  |                         |                   |
| (N)AS-2B  |                           | 3                      | 4                     | 0R1                      | 33K  | 0R5                            | 12K  |                         |                   |
| (N)AS-2C  |                           | 2                      | 3                     | 0R1                      | 18K  | 0R2                            | 7K5  |                         |                   |
| (N)AS-3   |                           | 3                      | 5                     | 0R1                      | 30K  | 0R5                            | 15K  |                         |                   |
| (N)AS-5   | RW74U                     | 5                      | 7                     | 0R1                      | 60K  | 0R8                            | 30K  |                         |                   |
| (N)AS-7   |                           | 7                      | 9                     | 0R1                      | 90K  | 1R0                            | 45K  |                         |                   |
| (N)AS-10  | RW78U                     | 10                     | 14                    | 0R1                      | 150K | 0R3                            | 51K  |                         |                   |

## Physical Data

| Dimensions Inches (mm) |                      |             |              |              |             |
|------------------------|----------------------|-------------|--------------|--------------|-------------|
| Type                   | A $\pm 0.032$ (0.81) | B (max)     | C (max)      | D (nom)      | E (min)     |
| (N)AS-1/4              | 0.250 (6.4)          | 0.094 (2.4) | 0.312 (7.9)  | 0.020 (0.5)  | 1.50 (38.1) |
| (N)AS-1/2              | 0.312 (7.9)          | 0.094 (2.4) | 0.375 (9.5)  | 0.020 (0.5)  | 1.50 (38.1) |
| (N)AS-1                | 0.367 (9.3)          | 0.125 (3.2) | 0.429 (10.9) | 0.020 (0.5)  | 1.50 (38.1) |
| (N)AS-1C               | 0.256 (6.5)          | 0.115 (2.9) | 0.303 (7.7)  | 0.025 (0.64) | 1.50 (38.1) |
| (N)AS-2                | 0.480 (12.2)         | 0.250 (6.3) | 0.600 (15.2) | 0.032 (0.8)  | 1.50 (38.1) |
| (N)AS-2B               | 0.540 (13.7)         | 0.219 (5.6) | 0.663 (16.6) | 0.032 (0.8)  | 1.30 (33.0) |
| (N)AS-2C               | 0.489 (11.0)         | 0.157 (4.0) | 0.594 (15.1) | 0.032 (0.8)  | 1.30 (33.0) |
| (N)AS-3                | 0.687 (17.5)         | 0.282 (7.2) | 0.812 (20.6) | 0.040 (1.0)  | 1.50 (38.1) |
| (N)AS-5                | 0.875 (22.2)         | 0.344 (8.8) | 0.980 (24.9) | 0.040 (1.0)  | 1.50 (38.1) |
| (N)AS-7                | 1.250 (31.8)         | 0.344 (8.8) | 1.375 (35.0) | 0.040 (1.0)  | 1.50 (38.1) |
| (N)AS-10               | 1.812 (46.0)         | 0.385 (9.8) | 1.937 (49.2) | 0.040 (1.0)  | 1.50 (38.1) |




### General Note

TT Electronics reserves the right to make changes in product specification without notice or liability.  
All information is subject to TT Electronics' own data and is considered accurate at time of going to print.


(N)AS Series

Performance Data


Power Derating




Temperature Rise @ 25°C



Temperature Rise @ 125°C



Selected Pulse-Handling Capability @ 125°C



Environmental Testing

| Test Condition            | Max ΔR |
|---------------------------|--------|
| Load Life 1000 hours      | 1.0%   |
| Moisture Resistance       | 1.0%   |
| Temperature Cycle         | 0.5%   |
| Short Time Overload       | 0.5%   |
| Low Temperature Operation | 0.5%   |
| Solder Heat               | 0.25%  |
| Shock                     | 0.5%   |
| Vibration                 | 0.5%   |

General Note

TT Electronics reserves the right to make changes in product specification without notice or liability.  
All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

(N)AS Series

Ordering Procedure

This product has two valid part numbers:

European (Welwyn) Part Number: AS3-27KFI (AS3, 27 kilohms ±1%, Pb-free)

|   |   |   |   |   |   |   |   |   |   |
|---|---|---|---|---|---|---|---|---|---|
|   | A | S | 3 | - | 2 | 7 | K | F | I |
| 1 | 2 | 3 | 4 | 5 |   |   |   |   |   |

| 1                 | 2                                                                     | 3                                               | 4         | 5                                   |          |
|-------------------|-----------------------------------------------------------------------|-------------------------------------------------|-----------|-------------------------------------|----------|
| Winding           | Type                                                                  | Value                                           | Tolerance | Termination & Packing               |          |
| Omit for standard | AS1/4, AS1/2<br>AS1, AS1C<br>AS2, AS2B<br>AS2C, AS3<br>AS5, AS7, AS10 | E24 = 3/4 characters<br>R = ohms<br>K = kilohms | D = ±0.5% | I = Pb-free, Standard packing bulk* |          |
| N = non-inductive |                                                                       |                                                 | F = ±1%   | AS1/4, 1/2, 1, 1C, 2, 2B, 2C, 3, 5  | 1000/box |
|                   |                                                                       |                                                 | H = ±3%   |                                     |          |
|                   |                                                                       |                                                 | J = ±5%   | AS7, 10                             | 500/box  |

\* Tape and reel available on request

USA (IRC) Part Number: AS32702FLF (AS3, 27 kilohms ±1%, Pb-free)

|   |   |   |   |   |   |   |   |   |   |   |
|---|---|---|---|---|---|---|---|---|---|---|
|   | A | S | 3 | 2 | 7 | 0 | 2 | F | L | F |
| 1 | 2 | 3 | 4 | 5 |   |   |   |   |   |   |

| 1                 | 2                                                                     | 3                             | 4         | 5                                 |          |
|-------------------|-----------------------------------------------------------------------|-------------------------------|-----------|-----------------------------------|----------|
| Winding           | Type                                                                  | Value                         | Tolerance | Termination & Packing             |          |
| Omit for standard | AS1/4, AS1/2<br>AS1, AS1C<br>AS2, AS2B<br>AS2C, AS3<br>AS5, AS7, AS10 | 3 digits + multiplier         | D = ±0.5% | LF=Pb-free, Omit for SnPb         |          |
| N = non-inductive |                                                                       |                               | F = ±1%   | Standard packing bulk*            |          |
|                   |                                                                       | R = ohms for values <100 ohms | H = ±3%   | AS1/4, 1/2, 1, 1C, 2, 2B 2C, 3, 5 | 1000/box |
|                   |                                                                       |                               | J = ±5%   |                                   |          |
|                   |                                                                       |                               |           | AS7, 10                           | 500/box  |

\* Tape and reel available on request

General Note

TT Electronics reserves the right to make changes in product specification without notice or liability.  
All information is subject to TT Electronics' own data and is considered accurate at time of going to print.