Data Sheet

HUBER+SUHNER

EMP Protector 3409.41.0085

Description

High-power/low-IM GDT hybrid technology

Benefits

Multi-band operation


DC continuity for remote powering

The protector can also be installed reversely

AISG compliant for 2.176 MHz carrier

Replaceable GDT 9071.99.0548, (90 V) included

Compliant to IEC 61643-21



Product Configuration

Main path connectors Port 1: <u>unprotected</u>, 7/16 jack (female) - Port 2: <u>protected</u>, 7/16 jack (female)

Mounting and grounding MH74 (bulkhead mounting), brk (bracket)

Side of bulkhead protected side

Technical Data

Electrical Data

Impedance 50Ω

2.176 MHz 820 - 2500 MHz 820 - 970 MHz 1700 - 2500 MHz Frequency range Return loss 20 dB typ. ≥ 20.8 dB ≥ 23.2 dB ≥ 23.2 dB Insertion loss 0.1 dB typ. ≤ 0.1 dB ≤ 0.1 dB ≤ 0.1 dB RF CW power ≤ 1500 W ≤ 3000 W ≤ 1500 W PIM 3rd order -150 dBc typ. -150 dBc typ. -150 dBc typ.

DC supply voltage ≤ 48 V
DC current ≤ 10 A

Surge current handling capability

30 single / 20 multiple kA (test pulse 8/20 µs)

Residual pulse energy 350 µJ typically (test pulse 4 kV 1.2/50 µs / 2 kA 8/20 µs) main path - protected side

Mechanical Data

Number of matings 100
Weight 260 g

Environmental Data

Operating temperature -40 °C to +85 °C

Waterproof degree IP65 (according to IEC 60529, data refer to the coupled state)

2011/65/EU (RoHS - including compliant acc. Annex III 2015/863 and 2017/2102)

Material Data

Piece Parts	Material	Surface Plating
Housing	Aluminium	Chromatized
Port 1 center contact	Bronze	Silver Plating
Port 2 center contact	Bronze	Silver Plating

Related Documents


Outline drawing DOU-00154641
Mounting instruction DOC-0000447876

Remarks

Ordering information for optional stainless steel mounting/grounding accessory:

9075.99.0108: threaded stud M8, length 30mm, hexagonal nut M8, washer and tooth washer

Recommendation: if this protector is mated with connectors made of copper-alloy base material and trimetal or nickel plating the connector area must be taped to improve long-term durability.



Data Sheet



EMP Protector 3409.41.0085

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

www.hubersuhner.com

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

HUBER+SUHNER:

3409.41.0085