

SPECIFICATION CONTROL DRAWING

55PC4233

TITLE

THREE CONDUCTOR CABLE, JACKETED, 600 VOLT

Date

06-04-01

Revision

A

This specification sheet forms a part of the latest issue of Raychem Specification 55PC.

COMPONENT WIRES - 55PC0213

JACKET - RADIATION-CROSSLINKED,
MODIFIED ETFE

CONSTRUCTION DETAILS

PART NUMBER	CONDUCTOR SIZE (AWG)	JACKET THICKNESS (in.)		DIAMETER (in.)			WEIGHT (lbs/1000 ft.)	
		LOWER SPEC LIMIT	TARGET WALL	LOWER SPEC LIMIT	TARGET VALUE	UPPER SPEC LIMIT	TARGET VALUE	UPPER SPEC LIMIT
55PC4233-24-*	24	.0055	.0070	.095	.100	.105	7.69	8.21
55PC4233-22-*	22	.0055	.0070	.108	.113	.118	10.69	11.28
55PC4233-20-*	20	.0060	.0075	.127	.132	.137	15.61	16.30
55PC4233-18-*	18	.0060	.0075	.148	.153	.158	22.65	23.50
55PC4233-16-*	16	.0060	.0080	.164	.170	.176	28.52	29.53
55PC4233-14-*	14	.0060	.0080	.197	.202	.208	42.77	44.03
55PC4233-12-*	12	.0060	.0080	.237	.244	.250	64.30	65.87
55PC4233-10-*	10	.0070	.0085	.289	.297	.305	100.27	102.77
55PC4233- 8-*	8	.0090	.0100	.426	.443	.458	183.96	194.46

CABLE RATINGS AND ADDITIONAL REQUIREMENTS

TEMPERATURE RATING: 200°C

Maximum continuous conductor temperature

VOLTAGE RATING: 600 volts (rms)

DIELECTRIC WITHSTAND: 1500 volts (rms)

CROSSLINK VERIFICATION: 300 ± 3°C for 1 hour

JACKET COLOR: White preferred

JACKET ELONGATION AND TENSILE STRENGTH:

Elongation, 50% (minimum)

Tensile Strength, 5000 lbf/in² (minimum)

PART NUMBER:

The "*" in the part numbers above shall be replaced by a color code designator with a slash separating the component wire colors and a dash separating the component wire colors from the jacket color.

Example: AWG 20, red, blue and yellow component wires; white jacket: 55PC4233-20-2/6/4-9

5/6 184

5/6 195

COLOR AND COLOR CODE DESIGNATORS SHALL BE IN ACCORDANCE WITH MIL-STD-681.

THIS SPECIFICATION SHEET TAKES PRECEDENCE OVER DOCUMENTS REFERENCED HEREIN. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATION FOR BID.

Raychem

300 Constitution Drive, Menlo Park, California 94025
1-800-2 Raychem FAX: 650-361-6297