


600G005
MIL-C-28840
Plug and Receptacle Holder



| Shell Size | Max. Recommended Torque (Inch Pounds) | A Dia. Max. | B Dia. Max. | C Dim. Max. |
|------------|---------------------------------------|--------------|--------------|-------------|
| 11 | 80 | .697 (17.7) | .502 (12.8) | .945 (24.0) |
| 13 | 110 | .822 (20.8) | .626 (15.9) | .945 (24.0) |
| 15 | 120 | .995 (25.3) | .798 (20.3) | .945 (24.0) |
| 17 | 120 | 1.058 (26.9) | .868 (22.0) | .945 (24.0) |
| 19 | 120 | 1.245 (31.6) | 1.035 (26.3) | .945 (24.0) |
| 23 | 140 | 1.433 (36.4) | 1.220 (31.0) | .945 (24.0) |
| 25 | 140 | 1.558 (39.6) | 1.381 (35.1) | .945 (24.0) |
| 29 | 150 | 1.745 (44.3) | 1.547 (39.3) | .945 (24.0) |
| 33 | 150 | 1.933 (49.1) | 1.739 (44.2) | .945 (24.0) |

APPLICATION NOTES

1. Metric dimensions (mm) are indicated in parentheses.
2. Material: Case hardened carbon steel with electroless nickel finish.
3. Receptacle and plug holder drives: 1/4" - Shell sizes 08, 10, 12; 3/8" - Shell sizes 14 and up.