

I. MATERIALS AND FINISHES:
FAKRA SMB PLUG: BODY - ZINC ALLOY, NICKEL PLATING
 CENTER CONTACT - BERYLLIUM COPPER, GOLD PLATING
AMC PLUG: BODY - PHOSPHOR BRONZE, SILVER PLATING
 CENTER CONTACT - PHOSPHOR BRONZE, GOLD PLATING
CABLE: 1.37MM MICRO-COAX

3. MECHANICAL:
A. RECOMMENDED LOCKWASHER TORQUE: 1.13 N-M [10 IN-LBS]

Technical drawing of the cable assembly showing side and end views. The side view on the left shows the cable connected to a FAKRA SMB PLUG. The end view on the right shows the cable connected to an AMC R/A PLUG. The cable is secured with a GASKET, LOCK WASHER, and 8MM HEX NUT. A HEAT SHRINK TUBE is shown over the cable. A dimension of 12.70 REF is indicated for the length of the cable. The overall length is labeled as LENGTH "L" (SEE TABLE).

PART NUMBER TABLE	
PART NUMBER	LENGTH "L" MM [IN]
95-820-109-05Y	50.00±5.00 [1.97±.20]
95-820-109-10Y	100.00±5.00 [3.94±.20]
95-820-109-15Y	150.00±5.00 [5.91±.20]
95-820-109-20Y	200.00±5.00 [7.87±.20]
95-820-109-25Y	250.00±5.00 [9.84±.20]
95-820-109-30Y	300.00±5.00 [11.81±.20]

FAKRA KEY TABLE			
KEY CODE	ASSEMBLY PART #	COLOR	RAL NO.
A	95-820-109-XXA	JET BLACK	9005
B	95-820-109-XXB	CREAM	9001
C	95-820-109-XXC	SIGNAL BLUE	5005
D	95-820-109-XXD	CLARET VIOLET	4004
E	95-820-109-XXE	LEAF GREEN	6002
F	95-820-109-XXF	NUT BROWN	8011
G	95-820-109-XXG	BLUE GREY	7031
H	95-820-109-XXH	HEATHER VIOLET	4003
I	95-820-109-XXI	BEIGE	1001
K	95-820-109-XXK	CURRY	1027
L	95-820-109-XXL	CARMINE RED	3002
M	95-820-109-XXM	PASTEL ORANGE	3003
N	95-820-109-XXN	PASTEL GREEN	6019
Z	95-820-109-XXZ	WATER BLUE	5021

☒ FREQUENCY: DC TO 6 GHz	☒ CONTINUITY
☒ VSWR : 1.30 MAX @ 2 GHz 1.50 MAX @ 6 GHz	☒ HI-POT :200 VRMS
☐ INS. LOSS ----- dB MAX	☐ OTHER

CUSTOMER OUTLINE DRAWING

ALL OTHER SHEETS ARE FOR INTERNAL USE ONLY

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN METRIC AND TOLERANCES ARE: <0.5mm 0.5 - 6mm 6 - 30mm 30 - 120mm ANGLES ± 0.05mm ±0.1mm ±0.2mm ± 0.3mm ±1°					MATERIAL		DRAWN		DATE		TITLE IP-67 FAKRA STR SMB PLUG TO AMC R/A PLUG ON 1.37MM CABLE, VARIOUS LENGTH				Amphenol RF www.amphenolrf.com			
NOTICE - These drawings, specifications, or other data (1) are, and remain the property of Amphenol corp. (2) must be returned upon request; and (3) are confidential and not to be disclosed to any person other than those to whom they are given by Amphenol Corp. the furnishing of these drawings, specifications, or other data by Amphenol Corp., or to any other person to anyone for any purpose is not to be regarded by implication or otherwise in any manner licensing, granting rights to permitting such holder or any other person to manufacture, use or sell any product, process or design, patented or otherwise, that may in any way be related to or disclosed by said drawings, specifications, or other data.					SEE NOTES		ENGINEER		DATE									
					REFERENCE		B. GREENBAUM		16-OCT-17									
					EAR# 8550		APPROVED		DATE		SCALE: 3.0:1.0		SHEET 2 OF 2					
					REF: TRUE		S. HSIEH		27-FEB-18									
CONFIGURATION LEVEL: In Work					CAD FILE		DWG SIZE				REV							
FINISH							B											
														DRAWING NO. 95-820-109-XXY				
														ITEM NO. 95-820-109-XXY				
														PART NO. 95-820-109-XXX				