



STANDARD LENGTHS ACCORDING TO CUSTOMER DRAWING 1206850	
PART NUMBER	"L" (meter)
X-2061980-Y	XY.0

PRELIMINARY PART

NOT RELEASED FOR PRODUCTION

THIS PRODUCT HAS NOT COMPLETED VALIDATION TESTING

NOTES:

1 MAX. CONNECTOR ATTENUATION 0.3 dB, MEASURED AT 1310 nm AND 1550 nm ACCORDING TO I.E.C. 61300-3-4 INSERTION METHOD B

2 MIN. RETURN LOSS 45 dB, IN MATED CONDITION AGAINST REFERENCE CONNECTOR AT 1310 nm AND 1550 nm

3 INFORMATION ON LABEL, SEE DETAIL FOR EXAMPLE

- BARCODE
- UNIQUE TE SERIAL NUMBER
- ASSEMBLY LENGTH
- TE CONNECTIVITY PART NUMBER & ORDER NUMBER

4 CABLE INFORMATION:

- CORE DIAMETER: 9/125 μ m (2x)
- OUTER JACKET DIAMETER: 4.8 mm
- OUTER JACKET COLOUR: BLACK
- OUTER JACKET MATERIAL: HALOGEN FREE FLAME RETARDANT
- CABLE ATTENUATION: 0.40 dB/km @ 1310 nm OR 0.25 dB/km @ 1550 nm

1	INFORMATION LABEL	7
1	LC DUPLEX CONNECTOR, SINGLE MODE, BLUE	6
2	PROTECTIVE TUBING, BLACK	5
1	HEAT SHRINK TUBING, BLACK	4
1	FULLAXS MINI LC DUPLEX PLUG ASSEMBLY, SM, WITH CAP, BLACK	3
1	FULLAXS MINI STOPPER, CABLE TIE	2
L	FOCAB Ø4.8 mm, 2FOLD, SINGLE MODE G657.A2, BLACK	1
Qty	Description	Item

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: mm

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC ± -

1 PLC ± -

2 PLC ± -

3 PLC ± -

4 PLC ± -

ANGLES ± -

MATERIAL -

FINISH -

WEIGHT -

CUSTOMER DRAWING

DWN R. COOLEN

CHK -

APVD S. BORGAS

10DEC2014

27MAY15

NAME

PRODUCT SPEC

APPLICATION SPEC

SIZE A2

CAGE CODE 00779

DRAWING NO C=2061980

RESTRICTED TO -

SCALE NTS

SHEET 1 OF 1

REV 1

TE Connectivity

FIBER OPTIC LEAD 4.8 mm

FULLAXS MINI LC/DPX - LC/DPX

SINGLE MODE G657.A2

TE Connectivity

290420071111111 20 meter 0025051988

UNIQUE TE SERIAL NUMBER

TE CONNECTIVITY PART NUMBER

ASSEMBLY LENGTH

TE CONNECTIVITY ORDER NUMBER

3 LABEL DETAIL:

BAR CODE