

# PIN RECEPTACLES

## FOR .015" - .025" DIAMETER PINS


### 4011
**4011-0-15-XX-30-XX-04-0**
Press-fit in .057 mounting hole





### 1801
**1801-0-15-XX-30-XX-04-0**
Press-fit in .057 mounting hole.
Shell is Phosphor Bronze Alloy 544 (B2)





### 1001
**1001-0-15-XX-3X-XX-04-0**
Press-fit in .057 mounting hole





### 0156
**0156-0-18-XX-30-XX-04-0**
Self-retention socket pin .038 - .043
hole prior to soldering





### 0255
**0255-0-15-XX-30-XX-04-0**
Solder mount in .022 min. mounting hole





### 1109
**1109-0-15-XX-30-XX-04-0**
Hex press-fit in .057 plated through-hole





### 3013
**3013-0-15-XX-32-XX-04-0**
Press-fit in .057 mounting hole




### 0134
**0134-0-15-XX-3X-XX-04-0**
Press-fit in .057 mounting hole





### 0132/0135
**013X-0-15-XX-30-XX-04-0**
Press-fit in .057 mounting hole




| Basic Part Number | Length A |
|---|---|
| 0132-0 | .273 |
| 0135-0 | .183 |

### 0133/0147
**01XX-0-15-XX-30-XX-04-0**
Press-fit in .059 mounting hole




| Basic Part Number | Length A |
|---|---|
| 0133-0 | .382 |
| 0147-0 | .563 |

### SPECIFICATIONS:

**Shell Material:** Brass Alloy 360, 1/2 Hard

**Contact Material:** Beryllium Copper Alloy 172, HT

**Dimensions:** Inches

**Tolerances On:** Lengths: ± .005
Diameters: ± .002
Angles: ± 2°

RoHS-2 2011/65/EU

### ORDER CODE: XXXX - X - 15 - XX - XX - XX - 10 - 0

**BASIC PART #**

**SPECIFY SHELL FINISH:**
- **01** 200 µ" TIN/LEAD OVER NICKEL
- **80** 200 µ" TIN OVER NICKEL (RoHS)
- **15** 10 µ" GOLD OVER NICKEL (RoHS)

**SPECIFY CONTACT FINISH:**
- **02** 100 µ" TIN/LEAD OVER NICKEL
- **84** 100 µ" TIN OVER NICKEL (RoHS)
- **27** 30 µ" GOLD OVER NICKEL (RoHS)

**SELECT CONTACT:**
**#30 or #32** CONTACT (DATA ON PAGE 253)
(For alternate contact choices, see groups B and C on page 248)