




LOC	DIST	REVISIONS				
		P	LTR	DESCRIPTION	DATE	DWN
-	-	H		UPDATE PER ECO-11-013056	23 JUN 11	CAS
						MKS

- 1 CONNECTOR BODY AND JAM NUT MATERIAL: 6061-T6 ALUMINUM, ELECTROLESS NICKEL PLATED PER SAE-AMS-C-26074 OR SAE-AMS-2404E
LOCKING RING MATERIAL: BERYLLIUM COPPER, ELECTROLESS NICKEL PLATED PER SAE-AMS-C-26074 OR SAE-AMS-2404E
INSULATOR MATERIAL: LIQUID CRYSTAL POLYMER (LCP) PER ASTM D5138 OR POLYPHENYLENE SULFIDE (PPS) PER ASTM D4067
O-RING MATERIAL: FLUOROSILICONE
- 2 WIRE TERMINATION: 28 AWG SOLID, 30 AWG STRANDED WIRE OR SMALLER
- 3 LUBRICATE O-RING WITH PARKER SUPER-O-LUBE PRIOR TO INSTALLATION
- 4 THIS DRAWING PREVIOUSLY IDENTIFIED AS NANONICS 303-0030

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	M. STORRY	7 MAY 99	TE Connectivity	
		CHK	E. PAULUS	7 MAY 99		
		APVD	S. KAIN	26 JAN 00	NAME	
		PRODUCT SPEC			RECEPTACLE ASSEMBLY, CIRCULAR, PANEL MOUNT, THREADED COUPLING/ QUICK DISCONNECT, METAL 19 POSITION	
		APPLICATION SPEC			SIZE	RESTRICTED TO
		WEIGHT			A2	—
		CUSTOMER DRAWING			CAGE CODE	REV
					0PJN9	H
					DRAWING NO	
					C=1589061	
					SCALE	
					6:1	
					SHEET	
					1 OF 1	