

# TGL2201-SM

## Wideband Dual Stage VPIN Limiter



### Applications

- LNA Receiver Chain Protection
- Military Radar



### Product Features

- 2-12 GHz Passive, High Isolation Limiter
- Low Loss < 1.0 dB , X-band
- Return Loss > 10 dB
- Flat Leakage < 18 dBm
- Input Power CW Survivability up to 5W
- Integrated DC Block on both input and output
- Package dimensions 3.0 x 3.0 x 1.35 mm


### General Description

The TriQuint TGL2201-SM is a packaged dual stage GaAs VPIN Limiter that operates over the 2 to 12 GHz band. Vertical PIN diodes provide the limiting action at high input signal levels and low loss at small signals.

The TGL2201-SM is suitable for a variety of wideband systems such as LNA/receiver protection in radars, phased arrays, and jammers.

Lead-free and RoHS compliant

### Functional Block Diagram



### Pin Configuration

| Pin #        | Symbol    |
|--------------|-----------|
| 6, 7         | RF IN/OUT |
| 14, 15       | RF OUT/IN |
| 5, 8, 13, 16 | N/C       |
| 2, 3, 10, 11 | N/C       |
| 1, 4, 9, 12  | GND       |

### Ordering Information

| Part No.       | ECCN  | Description               |
|----------------|-------|---------------------------|
| TGL2201-SM     | EAR99 | Wideband VPIN Limiter     |
| TGL2201-SM T/R |       | Wideband VPIN Limiter T/F |

Standard Order Quantity = 100 pieces in a waffle pack

Standard T/R size = 500 pieces on a 7" reel.

### Specifications

#### Absolute Maximum Ratings

| Parameter                         | Rating        |
|-----------------------------------|---------------|
| Storage Temperature               | -55 to 150 °C |
| RF Input Power, CW, 50Ω, T = 25°C | 37 dBm        |
| Mounting Temperature              | 260 °C        |

Operation of this device outside the parameter ranges given above may cause permanent damage.

#### Recommended Operating Conditions

| Parameter         | Min | Typ | Max | Units |
|-------------------|-----|-----|-----|-------|
| Passive – no bias |     |     |     |       |

Electrical specifications are measured at specified test conditions. Specifications are not guaranteed over all recommended operating conditions.

#### Electrical Specifications

Test conditions unless otherwise noted: 25°C




| Parameter                   | Conditions          | Min | Typical | Max | Units |
|-----------------------------|---------------------|-----|---------|-----|-------|
| Operational Frequency Range |                     | 2   |         | 12  | GHz   |
| Insertion Loss              |                     |     | 0.5     | 1.0 | dB    |
| Input Return Loss           |                     | 10  | 12      |     | dB    |
| Output Return Loss          |                     | 10  | 12      |     | dB    |
| Output Power                | Input Power = 27dBm |     | +18     |     | dBm   |

# TGL220I-SM

Wideband Dual Stage VPIN Limiter



## Typical Performance




# TGL220 I-SM

Wideband Dual Stage VPIN Limiter

## Application Circuit

### Schematic




#### Notes:

1. A heatsink is recommended for high power operation (RF input > 1 W).

# TGL220I-SM

Wideband Dual Stage VPIN Limiter

## Pin Description



| Pin           | Symbol       | Description                                                                                                                                       |
|---------------|--------------|---------------------------------------------------------------------------------------------------------------------------------------------------|
| 6, 7          | RF<br>IN/OUT | Input or output, matched to 50 ohms                                                                                                               |
| 5, 8, 13, 16  | N/C          | No internal connection; should be left open on PCB                                                                                                |
| 14, 15        | RF<br>OUT/IN | Output or input, matched to 50 ohms                                                                                                               |
| 2, 3, 10, 11, | N/C          | No internal connection; may be grounded or left open on PCB                                                                                       |
| 1, 4, 9, 12   | GND          | Pins 1,4,9, and 12 connected to 17 (backside paddle) inside package.                                                                              |
| 17            | GND          | On PCB, multiple vias should be employed under 17 to minimize inductance and thermal resistance; see page 8 for suggested mounting configuration. |

# TGL2201-SM

Wideband Dual Stage VPIN Limiter




## Applications Information

### PC Board Layout

Top RF layer is 0.008" thick Rogers RO4003,  $\epsilon_r = 3.55$ . Metal layers are 1-oz copper. Microstrip 50  $\Omega$  line width is .0174". The microstrip line tapers to a 0.014" width at the connector interface. This PCB is designed for the Southwest Microwave end launch connector 1092-01A-5.

The pad pattern shown has been developed and tested for optimized assembly at TriQuint Semiconductor. The PCB land pattern has been developed to accommodate lead and package tolerances. Since surface mount processes vary from company to company, careful process development is recommended.


For further technical information, refer to the [TGL2201-SM](#) Product Information page.





### Mechanical Information (cont.)

#### Mounting Configuration



Notes:

1. Ground / thermal vias are critical for the proper performance of this device. Vias should use a .35mm (#80 / .0135") diameter drill and have a final plated thru diameter of 0.25 mm (.010").
2. Add as much copper as possible to inner and outer layers near the part to ensure optimal thermal performance.
3. For further technical information, refer to the [TGL2201-SM](#) Product Information page.





### Product Compliance Information

#### ESD Information



**Caution! ESD-Sensitive Device**

ESD Rating: Class 1B  
Value:  $\geq 500$  V and  $< 1000$  V  
Test: Human Body Model (HBM)  
Standard: JEDEC Standard JESD22-A114

#### MSL Rating

Level 3 at  $+260^{\circ}\text{C}$  convection reflow  
The part is rated Moisture Sensitivity Level 3 at  $260^{\circ}\text{C}$  per JEDEC standard IPC/JEDEC J-STD-020.

#### Solderability


Compatible with the latest version of J-STD-020, Lead free solder,  $260^{\circ}$

This part is compliant with EU 2002/95/EC RoHS directive (Restrictions on the Use of Certain Hazardous Substances in Electrical and Electronic Equipment).

This product also has the following attributes:

- Lead Free
- Halogen Free (Chlorine, Bromine)
- Antimony Free
- TBBP-A ( $\text{C}_{15}\text{H}_{12}\text{Br}_4\text{O}_2$ ) Free
- PFOS Free
- SVHC Free

### Recommended Soldering Temperature Profile



# TGL2201-SM

## Wideband Dual Stage VPIN Limiter



### Contact Information

For the latest specifications, additional product information, worldwide sales and distribution locations, and information about TriQuint:

Web: [www.triquint.com](http://www.triquint.com)  
Email: [info-sales@tqs.com](mailto:info-sales@tqs.com)

Tel: +1.972.994.8465  
Fax: +1.972.664.8504

For technical questions and application information:

Email: [info-mmw@tqs.com](mailto:info-mmw@tqs.com)

### Important Notice

The information contained herein is believed to be reliable. TriQuint makes no warranties regarding the information contained herein. TriQuint assumes no responsibility or liability whatsoever for any of the information contained herein. TriQuint assumes no responsibility or liability whatsoever for the use of the information contained herein. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the user. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for TriQuint products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information.

TriQuint products are not warranted or authorized for use as critical components in medical, life-saving, or life-sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.

Copyright © 2012 TriQuint Semiconductor, Inc. All rights reserved.