



**Flat Power-DIP4-pin type
with high capacity
up to 2A load current**

**PhotoMOS®
PD 1 Form A
(AQY27O)**



FEATURES

1. **Flat-Packaged type**
(W) 8.8 × (D) 9.3 × (H) 3.9 mm
(W) .346 × (D) .366 × (H) .154 inch
2. **High capacity of continuous load current 2A (AQY272)**
3. **High sensitivity and low on-resistance**
Max. 2A load can be controlled with 5mA input current. The on-resistance is low at typ. 0.11Ω (AQY272).



RoHS compliant

TYPICAL APPLICATIONS

- Measuring and Testing equipment
- IC Testers and Board Testers
- High speed inspection machines

TYPES

Type	Output rating*		Package	Part No.				Packing quantity				
	Load voltage	Load current		Through hole terminal	Surface-mount terminal							
				Tube packing style		Tape and reel packing style						
AC/DC dual use	60V	2.0A	Power-DIP4-pin	AQY272	AQY272A	AQY272AX	AQY272AZ	1 tube contains: 50 pcs. 1 batch contains: 1,000 pcs.	1,000 pcs.			
	100V	1.3A		AQY275	AQY275A	AQY275AX	AQY275AZ					
	200V	0.65A		AQY277	AQY277A	AQY277AX	AQY277AZ					
	400V	0.35A		AQY274	AQY274A	AQY274AX	AQY274AZ					

* Indicate the peak AC and DC values.

Note: The surface mount terminal indicator "A" and the packing style indicator "X" or "Z" are not marked on the device.

RATING

1. Absolute maximum ratings (Ambient temperature: 25°C 77°F)


Item		Symbol	AQY272(A)	AQY275(A)	AQY277(A)	AQY274(A)	Remarks
Input	LED forward current	I _F		50 mA			
	LED reverse voltage	V _R		5 V			
	Peak forward current	I _{FP}		1 A			f = 100 Hz, Duty factor = 0.1%
	Power dissipation	P _{in}		75 mW			
Output	Load voltage (peak AC)	V _L	60 V	100 V	200 V	400 V	
	Continuous load current	I _L	2.0 A	1.3 A	0.65 A	0.35 A	Peak AC, DC
	Peak load current	I _{peak}	6.0 A	4.0 A	2.0 A	1.0 A	100ms (1 shot), V _L = DC
	Power dissipation	P _{out}		700 mW			
Total power dissipation		P _T		750 mW			
I/O isolation voltage		V _{iso}		2,500 V AC			
Temperature limits	Operating	T _{opr}		-40°C to +85°C -40°F to +185°F			Non-condensing at low temperatures
	Storage	T _{stg}		-40°C to +100°C -40°F to +212°F			

PD 1 Form A (AQY27O)

2. Electrical characteristics (Ambient temperature: 25°C 77°F)

Item		Symbol	AQY272(A)	AQY275(A)	AQY277(A)	AQY274(A)	Condition
Input	LED operate current	I_{Fon}	Typical	1.0 mA			$I_L = 100 \text{ mA}$ $V_L = 10 \text{ V}$
			Maximum	3.0 mA			
	LED turn off current	I_{Foff}	Minimum	0.4 mA			$I_L = 100 \text{ mA}$ $V_L = 10 \text{ V}$
			Typical	0.9 mA			
Output	LED dropout voltage	V_F	Typical	1.25 V (1.16 V at $I_F = 10 \text{ mA}$)			$I_F = 50 \text{ mA}$
			Maximum	1.5 V			
	On resistance	R_{on}	Typical	0.11 Ω	0.23 Ω	0.7 Ω	2.1 Ω
			Maximum	0.18 Ω	0.34 Ω	1.1 Ω	3.2 Ω
Transfer characteristics	Off state leakage current	I_{Leak}	Maximum	10 μA			$I_F = 0 \text{ mA}, V_L = \text{Max.}$
	Turn on time*	T_{on}	Typical	2.46 ms	2.40 ms	1.12 ms	1.65 ms
			Maximum	5.0 ms			$I_F = 10 \text{ mA}, I_L = 100 \text{ mA}$ $V_L = 10 \text{ V}$
			Typical	5.64 ms	5.65 ms	2.57 ms	3.88 ms
			Maximum	10.0 ms			$I_F = 5 \text{ mA}, I_L = 100 \text{ mA}$ $V_L = 10 \text{ V}$
Transfer characteristics	Turn off time*	T_{off}	Typical	0.22 ms	0.21 ms	0.10 ms	0.08 ms
			Maximum	3.0 ms			$I_F = 5 \text{ mA or } 10 \text{ mA}, I_L = 100 \text{ mA}$ $V_L = 10 \text{ V}$
	I/O capacitance	C_{iso}	Typical	0.8 pF			$f = 1 \text{ MHz}$ $V_B = 0 \text{ V}$
			Maximum	1.5 pF			
Transfer characteristics	Initial I/O isolation resistance	R_{iso}	Minimum	1,000 MΩ			500 V DC
	Maximum operating speed	—	Maximum	0.5 cps			$I_F = 10 \text{ mA}, \text{Duty factor} = 50\%$ $I_L = \text{Max.}, V_L = \text{Max.}$

*Turn on/Turn off time



RECOMMENDED OPERATING CONDITIONS

Please obey the following conditions to ensure proper device operation and resetting.

Item	Symbol	Recommended value	Unit
Input LED current	I_F	5 to 10	mA

For Dimensions.

For Schematic and Wiring Diagrams.

For Cautions for Use.

These products are not designed for automotive use.


If you are considering to use these products for automotive applications, please contact your local Panasonic Corporation technical representative.

For more information.

REFERENCE DATA


1. Load current vs. ambient temperature characteristics

Allowable ambient temperature: -40°C to +85°C
-40°F to +185°F




2.- (1) On resistance vs. ambient temperature characteristics

LED current: 10 mA;
Continuous load current: 2.0 A (DC) (AQY272),
1.3 A (DC) (AQY275)



2.- (2) On resistance vs. ambient temperature characteristics


LED current: 10 mA;
Continuous load current: 0.65 A (DC) (AQY277),
0.35 A (DC) (AQY274)



PD 1 Form A (AQY27○)


3. Turn on time vs. ambient temperature characteristics

LED current: 10 mA; Load voltage: 10 V (DC); Continuous load current: 100 mA (DC)




4. Turn off time vs. ambient temperature characteristics

LED current: 10 mA; Load voltage: 10 V (DC); Continuous load current: 100 mA (DC)




5. LED operate vs. ambient temperature characteristics

Load voltage: 10 V (DC); Continuous load current: 100 mA (DC)




6. LED turn off current vs. ambient temperature characteristics

Load voltage: 10 V (DC); Continuous load current: 100 mA (DC)




7. LED dropout voltage vs. ambient temperature characteristics

Sample: all types; LED current: 5 to 50 mA




8. Current vs. voltage characteristics of output at MOS portion

Ambient temperature: 25°C 77°F




9.-1) Off state leakage current vs. load voltage characteristics

Ambient temperature: 25°C 77°F




9.-2) Off state leakage current vs. load voltage characteristics

Ambient temperature: 25°C 77°F




10. Turn on time vs. LED forward current characteristics

Load voltage: 10 V (DC); Continuous load current: 100 mA (DC); Ambient temperature: 25°C 77°F




11. Turn off time vs. LED forward current characteristics

Load voltage: 10 V (DC); Continuous load current: 100 mA (DC); Ambient temperature: 25°C 77°F




12.-1) Turn on time vs. load voltage characteristics

LED current: 10 mA; Continuous load current: 100 mA; Ambient temperature: 25°C 77°F



12.-2) Turn on time vs. load voltage characteristics


LED current: 10 mA; Continuous load current: 100 mA; Ambient temperature: 25°C 77°F



PD 1 Form A (AQY27O)


13.- (1) Turn on time vs. load current characteristics

LED current: 10 mA; Load voltage: 10 V (DC);
Ambient temperature: 25°C 77°F



13.- (2) Turn on time vs. load current characteristics

LED current: 10 mA; Load voltage: 10 V (DC);
Ambient temperature: 25°C 77°F




14.- (1) Turn off time vs. load voltage characteristics

LED current: 10 mA; Continuous load current:
100 mA; Ambient temperature: 25°C 77°F


14.- (2) Turn off time vs. load voltage characteristics

LED current: 10 mA; Continuous load current:
100 mA; Ambient temperature: 25°C 77°F




15.- (1) Turn off time vs. load current characteristics

LED current: 10 mA; Load voltage 10 V (DC);
Ambient temperature: 25°C 77°F




15.- (2) Turn off time vs. load current characteristics

LED current: 10 mA; Load voltage 10 V (DC);
Ambient temperature: 25°C 77°F




16. Maximum operating frequency vs. load voltage/current characteristics

Sample: All types; LED current: 10 mA;
Ambient temperature: 25°C 77°F



17. Output capacitance vs. applied voltage characteristics

Frequency: 1 MHz;
Ambient temperature: 25°C 77°F



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Panasonic:

[AQY272AX](#) [AQY272AZ](#) [AQY274AX](#) [AQY274AZ](#) [AQY275](#) [AQY275AX](#) [AQY275AZ](#) [AQY277](#) [AQY277AX](#)
[AQY277AZ](#) [AQY274A](#)