


DRAWING

 General tolerances : ± 0.5 mm

R. F. CHARACTERISTICS

FREQUENCY RANGE : DC – 4 GHz
 IMPEDANCE : 50Ω
 ATTENUATION NOMINAL : 20 dB

FREQUENCY	DC – 2 GHz	2 – 4 GHz
V.S.W.R.	≤ 1.20	≤ 1.30
DEVIATION (dB)	+ 0.5 / - 0.5	+ 0.5 / - 0.5


TEMPERATURE SENSITIVITY : $4 * (10^{-4} \text{ dB} / \text{dB} * ^\circ\text{C})$
 AVERAGE POWER HANDLING at 25° : 1 W
 PEAK POWER HANDLING(1 μ s , 1%) at 25° C : 100 W

MECHANICAL CHARACTERISTICS

CONNECTORS : 7/16 male / female per IEC 169-4
 WEIGHT : ≤ 205 g

ENVIRONNEMENTAL CHARACTERISTICS

OPERATING TEMPERATURE RANGE (°C) : - 40 ; + 85
 STORAGE TEMPERATURE RANGE (°C) : - 40 ; + 85

 Power derating
 Versus temperature


CREATION					
N°:					RADIALL
PEN/EP : H920016					101, rue P. Hoffmann
Name:M.G.					93116 ROSNY/BOIS
Date:24 Apr.96					France
Appr.: AF.	2 jun 99	New connector body	MG	AF	Tel : (33) 0149353535
	Issue	Revisions	Name	Appr.	Fax : (33) 0148546363