



Product Description

Portable Cordage, 2 Conductor 14AWG (41x30) Bare Copper, PVC Insulation, PVC Outer Jacket, UL Type SJTOW-A

Technical Specifications

Physical Characteristics (Overall)

AWG	Stranding	Material	No. of Co	nductors
14	41x30	BC - Bare Copper	2	
Condu	uctor Count:			2
Total I	Number of Pa	airs:		1

Material Nominal Wall Thickness PVC - Polyvinyl Chloride 0.033 in

Color Chart

Color	
Light Blue	
Brown	

Outer Shield Material

Material No Shield

Outer Jacket Material

Material	Material Trade Name	Nominal Diameter	Nominal Wall Thickness	Separator Material
PVC - Polyvinyl Chloride	Belflex®	0.348 in	0.032 in	Paper Tape

Construction and Dimensions

Type of Cordage:	SJTOW

Cabling

Filler Polypropylene

Electrical Characteristics

Current

Max. Recommended Current [A]
18 Amps per Conductor at 25°C (13 Amps over 50 ft)
13 Amps per Conductor at 25°C (over 50 ft)

Voltage

Dielectric Withstand Voltage UL Voltage Rating

1500 V AC Applied For 1 Min.	300 V RMS

Electrical Characteristics Notes:

tes: Dielectric Withstand Voltage: 1500 V AC Applied For 1 Min

Temperature Range

UL Temp Rating:	60°C
Operating Temp Range:	-35°C To +105

Mechanical Characteristics

Oil Resistance:	Yes
Bulk Cable Weight:	62 lbs/1000ft
Min Bend Radius/Minor Axis:	3.5 in

Standards

NEC/(UL) Compliance:	SJTOW
CSA AWM Compliance:	SJTOW

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2004-01-01
MII Order #39 (China RoHS):	Yes

Flammability, LS0H, Toxicity Testing

CSA Flammability: FT1 UL voltage rating: 300 V RMS	UL Flammability:	VW-1
UL voltage rating: 300 V RMS	CSA Flammability:	FT1
	UL voltage rating:	300 V RMS

Plenum/Non-Plenum

	Plenum (Y/N):	No
--	---------------	----

Part Number

Variants

Item #	Color	Putup Type	Lengti	h UPC
19508 B59250	Black, Matte	Reel	250 ft	612825127161
Footnote:				C - CRATE REEL P
Product Notes				
Product No	tes			
Notes:	tes		C	Dil Resistant Jacket

Update and Revision:

Revision Number: 0.308 Revision Date: 06-08-2020

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.