PIHER

PC-16 16 mm Carbon Potentiometer



Bushless version

FEATURES

- Carbon resistive element.
- IP54 protection according to IEC 60529.
- Polyester substrate.
- Modular gang type (up to 4).
- Self extinguishable material UL 94-V0.
- Upon request:
  - Metalic support.
  - Stereo matching.
  - Switch.
  - Nut & washer.
  - Bushless & shaftless models.
  - Assemblies with wires and connectors.

MECHANICAL SPECIFICATIONS

– Mechanical rotation angle:	300° ± 5°
– Electrical rotation angle:	280° ± 20°
– Torque:	0.5 to 1.5 Ncm. (0.7 to 2.1 in-oz)
– Stop torque:	> 40 Ncm. (>56 in-oz)
– Max. torque nut (binding out):	< 80 Ncm. (112 in-oz)
– Thrust and pull in the shaft:	> 25 N

* Others check availability.

** Up to 85°C depending on application.

ELECTRICAL SPECIFICATIONS

– Range of values*
100Ω ≤ Rn ≤ 5 M (Decad. 1.0 - 2.0 - 2.2 - 2.5 - 4.7 - 5.0)

– Standard tolerance*: 100Ω ≤ Rn ≤ 1M Ω ------ ± 20%
1MΩ < Rn ≤ 5M Ω ------ ± 30%

– Max. Voltage: 250 VDC (lin) 125 VDC (no lin)

– Nominal Power 50°C (122°F) (see power rating curve)
0.2 W (lin) 0.1 W (no lin)

– Taper* Lin ; Log; Alog (Log. & Alog. only Rn ≥ 1K).

– Residual resistance*: ≤ 0.5% Rn (5 Ω min.)

– Equivalent Noise Resistance: ≤ 3% Rn (3 Ω min.)

– Operating temperature**: –25°C + 70°C (–13°F + 158°F)

HOW TO ORDER

PC-16	D	H	10	I	M06	203	A	2020	OPTIONAL EXTRAS 0				

Serie
PC-16

Model
S =Single
D =Tandem
T =Triple
C =Quad.

Mounting style
H= Horizontal
V = Vertical
(See note 1)

Bushing diameter
07 = M7
10 = M10
SC = Bushless
(See note 2)

Terminals
I = PCB
C = Solder Lugs

Shafts
M04
M06
M07
M11
M17
P01
P22

(See note 3)

Value
101 = 100 Ω
203 = 20 K
504 = 500 K
505 = 5M
(See note 4)

Taper
A = Linear
B = Log.
C = Alog.
(See note 10)
Others tapers on request

Tolerance
0505 = ± 5%
1010 = ± 10%
2020 = ± 20%
3030 = ± 30%
(See note 5)

Shafts spec. leng.
XX.X
(See notes 6,9)

Mounting brackets
M1
M2
(See note 7)

Stereo matching
3D = 3dB
4D = 4dB
6D = 6dB
(See note 8)

Switch
I = PCB
C = Solder lugs
(See note 9)

Nuts & Washers
-TA = loose nut & washer
MTA=assembled nut & washer
-T- = loose nut
MT- = assembled nut
(See note 9)

NOTES:

(1) Mounting style: Type "V" is only available in model "S" potentiometer and with printed circuit terminals.

(2) Bushings: Type "10" has two paralell flat surfaces for avoiding rotation. Bushless option only available for single model.

(3) M07 shaft is only available with M10 bushing. --- = no shaft

(4) Value: • Code: 10 1 100 Ω
10 → 2 first digits of the value.
1 → Number of zeros
• In models "D", "T", "C", with different values, they will be asked by drawings.

(5) Tolerance (non standard), upon request. Example: +7% -5% Code: 07 05
07 → negative tolerance
05 → positive tolerance

(6) Shaft special length:
• Only for special length and plain shafts (not knurled). Example: Shaft Ø6.35 L= 24.5 M07 ..... 24.5
• NOTE: Maximun length recommended: L = 45
24.5 → special length shafts

(7) Mounting brackets: Only applicable for model "S", mounting "H" and without switch.

(8) Stereo matching: not available for single models. Maximun will be: •3dB for model "D" •4dB for model "T" •6dB for model "C"

(9) Not available for Bushless version.

(10) Switch option not available with antilog taper.

HOW TO ORDER CUSTOM DRAWING

PC-16 S V + DRAWING NUMBER (Max. 16 digits)

This way of ordering should be used for options which are not included in the "How to order" standard and optional extras.

STANDARD OPTIONS

Shaft length ..... 0 Standard Length
Mounting brackets ..... Without mounting brackets
Stereo matching ..... Only on request (see note 8)
Switch ..... No switch
Nut & washer ..... Without nut and washer

MODELS



PC-16 S/D/T/C..H...

PC-16 SV .....

METALLIC SUPPORT



PC-16 SH.....M1

PC-16 SH....M2

BUSHINGS



07

10

EXAMPLES OF BUSHLESS VERSION



Download STEP files here:
https://piher.net/piher/?p=938

TERMINALS





C





I

TAPERS

Standard

A = Linear
B = Log.
C = Alog.



POWER RATING CURVE



NUTS & WASHERS

Bushing 10



Bushing 07



NOTE = Please note relative terminal positions when ordering non linear tapers.

TESTS

		TYPICAL VARIATIONS
ELECTRICAL LIFE	1.000 h. @ 50°C; 0.2 W	±5 %
MECHANICAL LIFE : POT.* SWITCH	25.000 (10-15 CPM) 10.000 (1 A, 50 VAC)	±3 % (Rn < 1 MΩ)
TEMPERATURE COEFFICIENT	–25°C; +70°C	±300 ppm/°C (Rn < 100 KΩ)
THERMAL CYCLING	16 h. @ 85°C; 2h. @ –25°C	±2.5 %
DAMP HEAT	500 h. @ 40°C @ 95% HR	±5 %
VIBRATION (for each plane X,Y,Z)	2 h. @ 10 Hz. ... 55 Hz.	±2 %

(*) only applicable to values ≥1K. For lower values please consult.

SWITCH













PC-16S . . . H . . . . . . I / C





PC-16SV . . . I

SWITCH SPECIFICATIONS

NOMINAL CURRENT	1A, 250 VAC
CONTACT RESISTANCE (initial)	10 m Ω
OPERATING TORQUE	1 to 3 Ncm (1.4 to 4.2 in oz)
OPERATING ANGLE	30° ± 5°
TEST VOLTAGE	500 V

PACKAGING

Boxes of 100 pieces (single body model): Inner dimensions 250 x 160 x 95 mm

METALIC SHAFTS

STANDARD



A	L	CODE
4	45	M04
6	45	M06
6.35	45	M07



A	B	C	L	CODE
2	5	7	15	M11
2	10	11	20	M12
4	12	14	25	M13
4	12	14	30	M14
4	12	14	35	M15
4	12	14	40	M16
4	12	14	45	M17

SPECIAL



A
∅4
∅6
∅6.35

PLASTIC SHAFTS Ø3.1



P09

PLASTIC SHAFTS Ø4



P01



P02

PLASTIC SHAFTS Ø4



P04





P07





P08



P10



P21

PLASTIC SHAFTS Ø6

Shaft position shown full CCW. Any other position for plastic shafts has to be shiftted n times 24°. Other positions upon request.



P05



P06





P11



P12



P13





P14



P15



P16



P17



P18





P19



P20



P22

Special shaft example (18 teeth knurl & arrow. Check availability.).



OPEN CIRCUIT FEATURE (CUT TRACK)



CCW on-off (A)

PCI
Cut track at the beginning of the travel.



PCF
Cut track at the end of the travel





CW on-off (E)

A = Initial S = Wiper E = Final.
PCI, PCF and other configurations available upon request. Check the ordering code with Piher.

RECOMMENDED CONNECTIONS

Piher potentiometer's recommended connection circuit for a position sensor or control application.
(voltage divider circuit electronic design).



$R_L \geq 100 \times R$

Disclaimer

The product information in this catalogue is for reference purposes. Please consult for the most up to date and accurate design information.

Piher Sensors & Controls S.A., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Piher"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product described herein.

Piher disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Piher's terms and conditions of sale, including but not limited to the warranty expressed therein, which apply to these products.

No licence, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Piher.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Piher products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Piher for any damages arising or resulting from such use or sale. Please contact authorised Piher personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.

Information contained in and/or attached to this catalogue may be subject to export control regulations of the European Community, USA, or other countries. Each recipient of this document is responsible to ensure that usage and/or transfer of any information contained in this document complies with all relevant export control regulations. If you are in any doubt about the export control restrictions that apply to this information, please contact the sender immediately. For any Piher International Corp. Exports, Note: All products / technologies are EAR99 Classified commodities. Exports from the United States are in accordance with the Export Administration Regulations. Diversion contrary to US law is prohibited.

Piher is an Amphenol™ company.

Note: Piher products can be adapted to meet customer's requirements.
Due to continuous process improvement, specifications are subject to change without notice.

v180220

Contact

Piher Sensors & Controls SA
Polígono Industrial Municipal
Vial T2, 22,
31500 Tudela - Spain.
t. +34-948-820450
f. +34-948-824050

sales@piher.net

www.piher.net