

Product: 6321UE ☑



Security & Sound, 3 Conductor 18 AWG BC, Plenum

Product Description

Security & Commercial Audio Cable, 3 Conductor 18 AWG solid bare copper conductors with Flamarrest® insulation, Plenum, Flamarrest® jacket with ripcord.

Technical Specifications

PVC-LS - Polyvinyl Chloride (Low Smoke) Flamarrest®

Product Overview

Suitable Applications:			Intercom/PA Systems, Sound/Audio Systems			
Phys	Physical Characteristics (Overall)					
Conductor						
AWG	Stranding	Material	No. of Conducto	rs		
18	Solid	BC - Bare Copper	3			
Condu	ctor Count:			3		
Insulat	nsulation					
	Ma	aterial	Material Trac	le Name	Nominal Wall Thickness	

0.009 in

Color Chart

Number	Color
1	Black
2	Red
3	White

Outer Shield Material



Outer Jacket Material

Material	Material Trade Name	Nominal Diameter	Nominal Wall Thickness	Ripcord
PVC-LS - Polyvinyl Chloride (Low Smoke)	Flamarrest®	0.156 in	0.015 in	Yes

Construction and Dimensions

Cabling



Electrical Characteristics

Conductor DCR



Capacitance

Nom. Capacitance Conductor to Conductor 29 pF/ft

Current

Max. Recommended Current [A]

5 Amps per conductor @ 25°C

Voltage

UL Voltage Rating

300 V RMS

Temperature Range

UL Temp Rating:	75°C
Operating Temp Range:	0°C To +75°C

Mechanical Characteristics

Bulk Cable Weight:	22.2 lbs/1000ft
Max Recommended Pulling Tension:	58.8 lbs
Min Bend Radius/Minor Axis:	1.5 in

Standards

NEC Articles:		800
NEC/(UL) Specifica	tion:	CMP
CEC/C(UL) Specific	ation:	CMP

Applicable Environmental and Other Programs

Environmental Space:	Indoor - Plenum
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01
MII Order #39 (China RoHS):	Yes

Flammability, LS0H, Toxicity Testing

C(UL) Flammability:	FT6
UL Flammability:	NFPA 262
UL voltage rating:	300 V RMS

Plenum/Non-Plenum

Plenum (Y/N):	Yes

Part Number

Non-Plenum Number:	5321UE	

Variants

	ltem #	Color	Putup Type	Length	UPC
	6321UE 8771000	Natural	Reel	1,000 ft	612825426875
	6321UE 877Z1000	Natural	ReelTuff Box	1,000 ft	612825176268
İ	Footnote:				C - CRATE

History

Update and Revision: Revision Number: 0.266 Revision Date: 04-28-2020

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.