# Product datasheet Characteristics

# 9001SKR5R05H5

Bezel material	Black plastic
Device short name	К
Enclosure type	Weatherproof enclosure dust and oil resistant indoor/outdoor Enclosure corrosion resistance indoor/outdoor
Light source	Without
Mounting diameter	1.18 in (30 mm)
Operator additional information	Without guard Snap-in plastic mushroom 2.25 in

# Complementary

Line Rated Current	10 A	
Cap/operator or lens colour	Red	
Contact operation	Standard fingersafe	
Contacts type and composition	1 NO	
Control type	Push-button	
Electrical connection	Screw clamp terminal	
Light block supply	Without supply	
Marking	EMERGENCY STOP	
Mounting support	Panel	
Operator position information	2 positions	
Operator profile	1 projecting push-button	
Permissible voltage	<= 600 V	
Shape	Round head	_
Type of operator	Momentary	
Utilisation category	AC-15	
	DC-13	

#### **Environment**

NEMA degree of protection	NEMA 1/2/3/3R/4/4X/6/12/13	-
product certifications	CE	-
	UL listed file E42259 CCN NKCR	9
	CSA LR24590 class 3211 03	

## Offer Sustainability

WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:
Nickel compounds, which is known to the State of California to cause cancer, and	Nickel compounds, which is known to the State of California to cause cancer, and
Di-isodecyl phthalate (DIDP), which is known to the Sta of California to cause birth defects or other reproductive harm.	teDi-isodecyl phthalate (DIDP), which is known to the State of California to cause birth e defects or other reproductive harm.
For more information go to www.p65warnings.ca.gov	For more information go to www.p65warnings.ca.gov

### Contractual warranty

|--|