

Coaxial Cable Connector

11_716-50-3-3/003_-

Description

Straight cable plug

Interface standards

IEC 61169-4_CECC 22190_DIN 47223_VG 95250



Technical Data

Electrical Data

Impedance	50 Ω
Interface frequency max.	7.5 GHz
Frequency range	DC to GHz

Mechanical Data

Centre contact	soldered
Outer contact	soldered
Weight	0.0828 kg

Environmental Data

Operating temperature	-40 °C to 100 °C
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Brass	Silver Plating
Outer contact	Brass	Silver Plating
Body	Brass	Silver Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating
Gasket	VMQ (Silicone rubber)	

Related Documents

Outline drawing	DOU-00015776
Catalogue drawing	DCA-00292702
Assembly instruction	DOC-0000196279

Ordering Information

Tray package	11_716-50-3-3/003_-Y
--------------	----------------------

Additional Information

Suitable cables	SUCOFORM_141_CU, EZ_141_M17, MULTIFLEX_141
-----------------	--

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[HUBER+SUHNER:](#)

[11_716-50-32-4/033_-E](#)