

LOC	DIST	REVISIONS					
		P	LTR	DESCRIPTION	DATE	DWN	APVD
1	-		B1	REVISED PER ECR-13-003447	11MAR2013	RS	DD
			E	REVISED PER ECR-16-005692	02JUN2016	RS	JL
			F	REVISED PER ECR-16-017348	24FEB2017	RK	JL

D

C

B





A

D

C

B

A



P/N 293387-1 AS SHOWN

- Remarks:
- 1. cavities designed for MQS pin contact PN 1740335-x
 - 2. Counterpart is Plug PN 293388-x
 - 3. Polarity marking +/- permanent / usable for DC version
 - 4. PN specific marking
 - 5. PBT 15GF, UL 94 V0 WHITE COLOR

Keying HV-3	Keying HV-4
Keying LV-2	Keying HV-5

	LV-2	WHITE 5	LOW -VOLTAGE 125VAC /VDC	7A/125VAC /VDC =	293387-4
	HV-5	WHITE 5	HIGH-VOLTAGE 125V AC	6A/125V AC ~	293387-3
	HV-4	WHITE 5	HIGH-VOLTAGE 125V AC	6A/125V AC ~	293387-2
	HV-3	WHITE 5	HIGH-VOLTAGE 125V AC	6A/125V AC ~	293387-1
Note	Keying	COLOR/MATERIAL	REMARKS	Marking 4	PN

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN A. Vecchia 12FEB2009	TE Connectivity		
DIMENSIONS: mm		CHK G. Turco 12FEB2009			
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD G. Turco 12FEB2009	NAME NECTOR S Lighting System Outlet		
0 PLC ±0.2		PRODUCT SPEC	SIZE A2 CAGE CODE 00779 DRAWING NO C-293387 RESTRICTED TO -		
1 PLC ±0.13		APPLICATION SPEC			
2 PLC ±0.013		WEIGHT 2.2g	SCALE 3:1 SHEET 1 OF 1 REV F		
3 PLC ±0.0001		CUSTOMER DRAWING			
4 PLC ±0.0001					
ANGLES					
FINISH					