








REV.	ECN NO.	DATE	SIGN	DESCRIPTION
B	C190411	2019/03/18	Vicky	Change Note



Pin Assignments
Front View




Recommended Panel Cut-out



Note:

- * QC Important Dimension To Check.
- * Waterproof Rate: IP68, Unmated.
In 1 meter water within 24 hours
- * Housing: Thermoplastic, Black.
- * Pin: Copper Alloy, Gold Plated.
- * Nut: Thermoplastic, Black.
- * Gasket: Rubber, Gray.
- * Panel Thickness Maximum: 4.5mm
- * Gasket and Nut are packed separately in PE bags.

UNIT:mm



TOLERANCE
X ±0.25

TITLE
X Lok B-Size Receptacle
Rear Fastened M Conn M 2 Pin

SCALE
2:1

SIZE
A4

SHEET
1 OF 1

REV.
B

WC-REV.
A.1

QC : Inspection item

Amphenol LTW
安費諾亮泰企業股份有限公司

ITEM NO
BB-02RMMS-QC800P

DRAWN BY
Vicky

DATE
2019-03-18

DWG NO
BB-02RMMS-QC800P

CHECKED BY
Rita

DATE
2019-03-18

CUSTOMER
ALTW

APPROVED BY
Max

DATE
2019-03-18