



SPECIFICATIONS		
SILIKROME®	GRADE	
	COMMERCIAL	MILITARY
Material	Silicone Rubber ASTM D 1418	Silicone Rubber conforming to A-A-59588 Class II GR 50
Temperature Range	-112°F to +400°F (-80°C to +204°C)	-160°F to +450°F (-106°C to +260°C)
	-112°F to +575°F (-80°C to +302°C)	
Shelf Life	25 Years (minimum)	
Resistant to	Salt spray, sunlight, ozone, cleaning solutions, and most acids	
Physical Characteristics	Flexible, non-breakable, re-usable. Acts as shock mount. Protects against shattering. Easy to mount.	



SECTION AA

C	REDRAWN and MAT'L CHANGED	S. GOK	05.28.09
B	CAD COMPUTER GENERATED		01.10.03
A	REDESIGNED & REDRAWN	NICK	05.07.73
REV.	DESCRIPTION		DATE
MAXIMUM AND MINIMUM MEASUREMENTS ARE STATED DIRECTLY ON EACH DIMENSION. MAT'L: SEE ABOVE	TITLE: SILIKROMES® COLORED FILTERS FOR INCANDESCENT T-3 1/4 LAMPS	ENG. S. GOK	05.28.09
		DWN. NKS	09.09.66
		CHKD. J. CELLA	05.28.09
COLOR: SPECIFY	APM-HEXSEAL CORPORATION	SCALE 4 : 1	DWG. NO. 1813/27

THIS DRAWING COVERS PROPRIETARY ITEM AND IS THE PROPERTY OF THE APM-HEXSEAL CORPORATION.
THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE WRITTEN APPROVAL OF AN OFFICER OF THE APM-HEXSEAL CORPORATION.