INTERCHANGEABLE WALL PLUG POWER SUPPLY 6VDC 12WATT



T6329ST

Features:

- Interchangeable AC Heads
- 1 Year Warranty
- Level VI Efficiency
- Worldwide Approvals



Description:

The Stontronics range of 12Watt Interchangeable wall plug power supplies provide 12 watts of continuous power with the flexibility of worldwide usage as they are supplied with UK, Euro, USA & Auz AC Heads , all Efficiency Level VI and carry worldwide safety approvals.

| Specification | |
|--------------------------|--|
| Part Code | T6329ST |
| Input Voltage Range | 90-264 Vac |
| Input Frequency Range | 47-63Hz |
| Input Current Rated | 0.1A Max |
| Input AC Heads | UK, Euro, USA & Auz |
| Output Voltage Rating | +6V |
| Output Current Range | 2A |
| Output Min Current | 0A |
| Output Connection Type | 2.1x5.5x12mm centre positive – Right angle |
| Total Output Regulation | +/- 5% |
| Line and Load Regulation | +/- 5% |
| Ripple & Noise | 200mVp-p |
| Efficiency | 83%Min |
| Over Voltage Protection | Auto Recovery |
| Over Load Protection | Auto Recovery |
| Operating Temperature | 0 to 40°C |
| Storage Temperature | -20 to +70°C |
| Operating Humidity | 20 to 85% |
| Storage Humidity | 10 to 95% |
| Hi-Pot | Primary to Secondary :AC 3000Vrms, 4 mA , 1 minute for type test |
| Leakage Current | 0.25mA max |
| Safety Standard | CE, C-Tick, UL, TUV, GS |
| EMI Standard | Meets CE(EN55022) |
| MTBF | 50K Hours |
| Size mm max. | 71.38cm(L) x 40.95cm(W) x 34.31cm(H) |
| Weight | 68 g |

INTERCHANGEABLE WALL PLUG POWER SUPPLY 6VDC 12WATT



T6329ST

Diagrams

