

## RXK Series

### Features

- 105°C, 2,000 ~ 5,000 hours assured
- Low ESR, suitable for switching power supplies
- Smaller size with large permissible ripple current
- RoHS Compliance




Sleeve & Marking Color: Black & Golden

### Specifications

Items	Performance																																					
Category Temperature Range	-55°C ~ +105°C																																					
Capacitance Tolerance	±20% (at 120Hz, 20°C)																																					
Leakage Current (at 20°C)	I = 0.01CV or 3 (μA) whichever is greater (after 2 minutes) Where, C = rated capacitance in μF, V = rated DC working voltage in V																																					
Tanδ (at 120Hz, 20°C)	<table border="1"> <tr> <td>Rated Voltage</td> <td>6.3</td> <td>10</td> <td>16</td> <td>25</td> <td>35</td> <td>50</td> <td>63</td> </tr> <tr> <td>Tanδ (max)</td> <td>0.22</td> <td>0.19</td> <td>0.16</td> <td>0.14</td> <td>0.12</td> <td>0.10</td> <td>0.09</td> </tr> </table> <p>When the capacitance exceeds 1,000μF, 0.02 shall be added every 1,000μF increase.</p>	Rated Voltage	6.3	10	16	25	35	50	63	Tanδ (max)	0.22	0.19	0.16	0.14	0.12	0.10	0.09																					
Rated Voltage	6.3	10	16	25	35	50	63																															
Tanδ (max)	0.22	0.19	0.16	0.14	0.12	0.10	0.09																															
Low Temperature Characteristics (at 120Hz)	<p>Impedance ratio shall not exceed the values given in the table below.</p> <table border="1"> <tr> <td>Rated Voltage</td> <td>6.3</td> <td>10</td> <td>16</td> <td>25</td> <td>35</td> <td>50</td> <td>63</td> </tr> <tr> <td>Impedance Ratio</td> <td>Z(-55°C)/Z(+20°C)</td> <td>4</td> <td>4</td> <td>3</td> <td>3</td> <td>3</td> <td>3</td> </tr> </table>	Rated Voltage	6.3	10	16	25	35	50	63	Impedance Ratio	Z(-55°C)/Z(+20°C)	4	4	3	3	3	3																					
Rated Voltage	6.3	10	16	25	35	50	63																															
Impedance Ratio	Z(-55°C)/Z(+20°C)	4	4	3	3	3	3																															
Endurance	<table border="1"> <tr> <td>Test Time</td> <td>2,000 Hrs for φD ≤ 6.3 mm; 3,000 Hrs for φD = 8 mm; 4,000 Hrs for φD = 10 mm; 5,000 Hrs for φD ≥ 12.5 mm</td> </tr> <tr> <td>Capacitance Change</td> <td>Within ±20% of initial value</td> </tr> <tr> <td>Tanδ</td> <td>Less than 200% of specified value</td> </tr> <tr> <td>Leakage Current</td> <td>Within specified value</td> </tr> </table> <p>* The above specifications shall be satisfied when the capacitors are restored to 20°C after the rated voltage applied with rated ripple current for 2,000 ~ 5,000 hours at 105°C.</p>	Test Time	2,000 Hrs for φD ≤ 6.3 mm; 3,000 Hrs for φD = 8 mm; 4,000 Hrs for φD = 10 mm; 5,000 Hrs for φD ≥ 12.5 mm	Capacitance Change	Within ±20% of initial value	Tanδ	Less than 200% of specified value	Leakage Current	Within specified value																													
Test Time	2,000 Hrs for φD ≤ 6.3 mm; 3,000 Hrs for φD = 8 mm; 4,000 Hrs for φD = 10 mm; 5,000 Hrs for φD ≥ 12.5 mm																																					
Capacitance Change	Within ±20% of initial value																																					
Tanδ	Less than 200% of specified value																																					
Leakage Current	Within specified value																																					
Shelf Life Test	<table border="1"> <tr> <td>Test Time</td> <td>1,000 Hrs</td> </tr> <tr> <td>Capacitance Change</td> <td>Within ±20% of initial value</td> </tr> <tr> <td>Tanδ</td> <td>Less than 200% of specified value</td> </tr> <tr> <td>Leakage Current</td> <td>Within specified value</td> </tr> </table> <p>* The above specifications shall be satisfied when the capacitors are restored to 20°C after exposing them for 1,000 hours at 105°C without voltage applied.</p>	Test Time	1,000 Hrs	Capacitance Change	Within ±20% of initial value	Tanδ	Less than 200% of specified value	Leakage Current	Within specified value																													
Test Time	1,000 Hrs																																					
Capacitance Change	Within ±20% of initial value																																					
Tanδ	Less than 200% of specified value																																					
Leakage Current	Within specified value																																					
Ripple Current and Frequency Multipliers	<table border="1"> <tr> <td></td> <td>Freq.(Hz)</td> <td>60 (50)</td> <td>120</td> <td>500</td> <td>1k</td> <td>10k</td> <td>100k</td> </tr> <tr> <td rowspan="4">Cap.(μF)</td> <td>Under 33</td> <td>0.40</td> <td>0.55</td> <td>0.65</td> <td>0.80</td> <td>0.90</td> <td>1.00</td> </tr> <tr> <td>39 ~ 330</td> <td>0.60</td> <td>0.70</td> <td>0.80</td> <td>0.90</td> <td>0.95</td> <td>1.00</td> </tr> <tr> <td>390 ~ 1,000</td> <td>0.65</td> <td>0.80</td> <td>0.85</td> <td>0.98</td> <td>1.00</td> <td>1.00</td> </tr> <tr> <td>1,200 up above</td> <td>0.80</td> <td>0.90</td> <td>0.95</td> <td>0.98</td> <td>1.00</td> <td>1.00</td> </tr> </table>		Freq.(Hz)	60 (50)	120	500	1k	10k	100k	Cap.(μF)	Under 33	0.40	0.55	0.65	0.80	0.90	1.00	39 ~ 330	0.60	0.70	0.80	0.90	0.95	1.00	390 ~ 1,000	0.65	0.80	0.85	0.98	1.00	1.00	1,200 up above	0.80	0.90	0.95	0.98	1.00	1.00
	Freq.(Hz)	60 (50)	120	500	1k	10k	100k																															
Cap.(μF)	Under 33	0.40	0.55	0.65	0.80	0.90	1.00																															
	39 ~ 330	0.60	0.70	0.80	0.90	0.95	1.00																															
	390 ~ 1,000	0.65	0.80	0.85	0.98	1.00	1.00																															
	1,200 up above	0.80	0.90	0.95	0.98	1.00	1.00																															

Radial


### Diagram of Dimensions



Lead Spacing and Diameter Unit: mm

φD	5	6.3	8	10	12.5	16	18
P	2.0	2.5	3.5	5.0	5.0	7.5	7.5
φd	0.5		0.6		0.8		
α	L < 20: 1.5, L ≥ 20: 2.0						
β	0.5						

The case size of 16×20 is suitable for below diagram:





Dimension:  $\phi D \times L$ (mm)

Ripple Current: mA/rms at 100k Hz, 105°C

Dimension and Permissible Ripple Current

Cap. ( $\mu$ F)	Contents	6.3V (0J)				10V (1A)				16V (1C)						
		$\phi D \times L$	Impedance ( $\Omega$ , max./100k Hz)		Ripple Current (mA/rms, 105°C)		$\phi D \times L$	Impedance ( $\Omega$ , max./100k Hz)		Ripple Current (mA/rms, 105°C)		$\phi D \times L$	Impedance ( $\Omega$ , max./100k Hz)		Ripple Current (mA/rms, 105°C)	
			20°C	-10°C	120 Hz	100k Hz		20°C	-10°C	120 Hz	100k Hz		20°C	-10°C	120 Hz	100k Hz
56												5×11	0.72	1.8	116	165
68												5×11	0.72	1.8	126	180
82						5×11	0.72	1.8	116	165						
100						5×11	0.72	1.8	126	180						
120		5×11	0.72	1.8	116	165						6.3×11	0.38	0.95	179	255
180							6.3×11	0.38	0.95	179	255	6.3×15	0.27	0.68	231	330
220		6.3×11	0.38	0.95	179	255	6.3×11	0.38	0.95	196	280					
270		6.3×11	0.38	0.95	196	280	6.3×15	0.27	0.68	231	330	8×11.5	0.20	0.50	291	415
330		6.3×15	0.27	0.68	231	330	8×11.5	0.20	0.50	291	415	10×12.5	0.12	0.30	438	625
390		8×11.5	0.20	0.50	332	415	8×11.5	0.20	0.50	360	450	8×11.5	0.20	0.50	315	450
470		8×11.5	0.20	0.50	360	450	10×12.5	0.12	0.30	500	625	8×15	0.16	0.40	347	495
560		8×15	0.16	0.40	396	495	8×15	0.16	0.40	472	590	10×12.5	0.12	0.30	540	675
680		10×16	0.084	0.21	660	825	8×15	0.16	0.40	472	590	10×16	0.084	0.21	660	825
820		8×15	0.16	0.40	472	590	8×20	0.11	0.28	512	640	8×20	0.11	0.28	560	700
1,000		8×20	0.11	0.28	560	700	10×16	0.084	0.21	660	825	10×16	0.084	0.21	660	825
1,200		10×20	0.062	0.16	936	1,040	10×20	0.062	0.16	1,017	1,130	10×20	0.062	0.16	1,017	1,130
1,500		10×20	0.062	0.16	1,017	1,130	10×25	0.052	0.13	1,134	1,260	10×25	0.052	0.13	1,134	1,260
1,800		10×25	0.052	0.13	1,251	1,390	10×30	0.044	0.11	1,296	1,440	10×30	0.044	0.11	1,296	1,440
2,200		10×30	0.044	0.11	1,296	1,440	12.5×20	0.046	0.12	1,305	1,450	12.5×20	0.046	0.12	1,305	1,450
2,700		12.5×20	0.046	0.12	1,305	1,450	12.5×25	0.034	0.085	1,521	1,690	12.5×25	0.034	0.085	1,521	1,690
3,300		12.5×25	0.034	0.085	1,629	1,810	12.5×30	0.030	0.075	1,755	1,950	12.5×30	0.030	0.075	1,755	1,950
3,900		12.5×30	0.030	0.075	1,755	1,950	12.5×35	0.027	0.068	1,917	2,130	12.5×35	0.027	0.068	1,917	2,130
4,700		12.5×35	0.027	0.068	1,980	2,200	16×20	0.035	0.087	1,692	1,880	16×20	0.035	0.087	1,692	1,880
5,600		12.5×40	0.024	0.060	2,196	2,440	16×25	0.028	0.070	1,863	2,070	16×25	0.028	0.070	1,863	2,070
6,800		16×25	0.028	0.070	2,025	2,250	16×31.5	0.025	0.063	2,115	2,350	16×31.5	0.025	0.063	2,115	2,350
8,200		16×31.5	0.025	0.063	2,295	2,550	16×40	0.024	0.060	2,358	2,620	16×40	0.024	0.060	2,358	2,620
10,000		16×35.5	0.022	0.055	2,691	2,990	16×40	0.024	0.060	2,358	2,620	16×40	0.024	0.060	2,358	2,620

Radial



Dimension:  $\phi D \times L$ (mm)

Ripple Current: mA/rms at 100k Hz, 105°C

Dimension and Permissible Ripple Current

Rated Volt. $V_{DC}$ Cap. ( $\mu F$ )	Contents	25V (1E)				35V (1V)				50V (1H)						
		$\phi D \times L$	Impedance ( $\Omega$ , max./100k Hz)		Ripple Current (mA/rms, 105°C)		$\phi D \times L$	Impedance ( $\Omega$ , max./100k Hz)		Ripple Current (mA/rms, 105°C)		$\phi D \times L$	Impedance ( $\Omega$ , max./100k Hz)		Ripple Current (mA/rms, 105°C)	
			20°C	-10°C	120 Hz	100k Hz		20°C	-10°C	120 Hz	100k Hz		20°C	-10°C	120 Hz	100k Hz
18												5×11	1.1	3.3	72	130
22												5×11	1.1	3.3	83	150
27						5×11	0.72	1.8	91	165						
33						5×11	0.72	1.8	99	180						
39	5×11	0.72	1.8	116	165							6.3×11	0.56	1.6	154	220
47	5×11	0.72	1.8	126	180							6.3×11	0.56	1.6	161	230
56						6.3×11	0.38	0.95	179	255		6.3×15	0.41	1.2	217	310
68						6.3×11	0.38	0.95	196	280		8×11.5	0.29	0.84	238	340
82	6.3×11	0.38	0.95	179	255	6.3×15	0.27	0.68	231	330		8×11.5	0.29	0.84	249	355
												8×15	0.25	0.75	329	470
												10×12.5	0.16	0.40	336	480
100	6.3×11	0.38	0.95	196	280							10×12.5	0.16	0.40	371	530
120	6.3×15	0.27	0.68	231	330	8×11.5	0.20	0.50	291	415		8×15	0.25	0.75	392	560
						10×12.5	0.12	0.30	438	625		8×20	0.18	0.52	427	610
												10×16	0.12	0.30	529	755
150	8×11.5	0.20	0.50	291	415	8×11.5	0.20	0.50	315	450		10×16	0.12	0.30	588	840
						10×12.5	0.12	0.30	473	675						
180	8×11.5	0.20	0.50	315	450	8×15	0.16	0.40	347	495		8×20	0.18	0.52	525	750
	10×12.5	0.12	0.30	438	625							10×20	0.088	0.22	662	945
220	8×15	0.16	0.40	347	495	8×15	0.16	0.40	413	590		10×20	0.088	0.22	728	1,040
	10×12.5	0.12	0.30	473	675	8×20	0.11	0.28	448	640		10×25	0.068	0.17	805	1,150
						10×16	0.084	0.21	578	825						
270						8×20	0.11	0.28	490	700		10×25	0.068	0.17	896	1,280
						10×16	0.084	0.21	637	910						
330	8×15	0.16	0.40	413	590	10×20	0.062	0.16	728	1,040		10×30	0.059	0.15	882	1,260
	8×20	0.11	0.28	448	640							12.5×20	0.059	0.15	833	1,190
	10×16	0.084	0.21	578	825											
390	8×20	0.11	0.28	560	700	10×20	0.062	0.16	904	1,130		12.5×20	0.059	0.15	952	1,190
	10×16	0.084	0.21	728	910	10×25	0.052	0.13	1,008	1,260						
470	10×20	0.062	0.16	832	1,040	10×25	0.052	0.13	1,112	1,390		10×30	0.059	0.15	1,176	1,470
												12.5×25	0.045	0.11	1,192	1,490
560	10×20	0.062	0.16	904	1,130	10×30	0.044	0.11	1,152	1,440		12.5×25	0.045	0.11	1,304	1,630
	10×25	0.052	0.13	1,008	1,260	12.5×20	0.046	0.12	1,072	1,340		12.5×30	0.039	0.098	1,376	1,720
680	10×25	0.052	0.13	1,112	1,390	10×30	0.044	0.11	1,256	1,570		12.5×30	0.039	0.098	1,520	1,800
						12.5×20	0.046	0.12	1,160	1,450		12.5×35	0.033	0.083	1,512	1,900
						12.5×25	0.034	0.085	1,352	1,690		16×20	0.048	0.120	1,248	1,560
820	10×30	0.044	0.11	1,152	1,440	12.5×25	0.034	0.085	1,448	1,810		12.5×35	0.033	0.083	1,624	2,030
	12.5×20	0.046	0.12	1,072	1,340							12.5×40	0.029	0.073	1,656	2,070
												16×25	0.033	0.083	1,504	1,880
1,000	10×30	0.044	0.11	1,256	1,570	12.5×30	0.030	0.075	1,560	1,950		12.5×40	0.029	0.073	1,800	2,250
	12.5×20	0.046	0.12	1,160	1,450	16×20	0.035	0.087	1,376	1,720		16×25	0.033	0.083	1,664	2,080
	12.5×25	0.034	0.085	1,352	1,690						16×31.5	0.029	0.073	1,720	2,150	
1,200	12.5×25	0.034	0.085	1,629	1,810	12.5×30	0.030	0.075	1,917	2,130		16×31.5	0.029	0.073	2,088	2,320
						12.5×35	0.027	0.068	1,980	2,200		16×35.5	0.025	0.063	2,115	2,350
						16×25	0.028	0.070	1,863	2,070						
1,500	12.5×30	0.030	0.075	1,755	1,950	12.5×35	0.027	0.068	2,151	2,390		16×35.5	0.025	0.063	2,160	2,400
	16×20	0.035	0.087	1,539	1,710	12.5×40	0.024	0.060	2,196	2,440		16×40	0.021	0.063	2,336	2,595
						16×25	0.028	0.070	2,025	2,250						
1,800	12.5×30	0.030	0.075	1,917	2,130	12.5×40	0.024	0.060	2,358	2,620		16×40	0.021	0.063	2,466	2,740
	12.5×35	0.027	0.068	1,980	2,200	16×31.5	0.025	0.063	2,115	2,350		18×35.5	0.023	0.058	2,286	2,540
	16×25	0.028	0.070	1,863	2,070											
2,200	12.5×35	0.027	0.068	2,151	2,390	16×31.5	0.025	0.063	2,295	2,550		18×35.5	0.023	0.058	2,349	2,610
	12.5×40	0.024	0.060	2,196	2,440	16×35.5	0.022	0.055	2,295	2,550		18×40	0.020	0.050	2,385	2,650
	16×25	0.028	0.070	2,025	2,250											
2,700	16×31.5	0.025	0.063	2,115	2,350	16×35.5	0.022	0.055	2,394	2,660						
						16×40	0.018	0.045	2,610	2,900						
						18×35.5	0.021	0.053	2,448	2,720						
3,300	16×31.5	0.025	0.063	2,295	2,550	18×35.5	0.021	0.053	2,601	2,890						
	16×35.5	0.022	0.055	2,295	2,550	18×40	0.017	0.043	2,709	3,010						
3,900	16×35.5	0.022	0.055	2,394	2,660											
	16×40	0.018	0.045	2,610	2,900	18×40	0.017	0.043	2,934	3,260						
	18×35.5	0.021	0.053	2,448	2,720											
4,700	18×35.5	0.021	0.053	2,601	2,890											
	18×40	0.017	0.043	2,709	3,010											
5,600	18×40	0.017	0.043	2,934	3,260											

Radial



Dimension:  $\phi D \times L(\text{mm})$   
 Ripple Current: mA/rms at 100k Hz, 105°C

Dimension and Permissible Ripple Current

Cap. ( $\mu\text{F}$ )	Contents	63V(1J)				
		$\phi D \times L$	Impedance ( $\Omega$ , max./100k Hz)		Ripple Current (mA/rms, 105°C)	
			20°C	-10°C	120 Hz	100k Hz
12	5×11	1.90	4.78	55	100	
27	6.3×11	1.10	2.78	88	160	
33	6.3×11	1.10	2.75	96	175	
39	6.3×15	0.62	1.55	161	230	
47	8×11.5	0.49	1.23	193	275	
56	8×11.5	0.49	1.23	203	290	
	10×12.5	0.27	0.675	294	420	
68	8×15	0.34	0.850	252	360	
	10×12.5	0.27	0.675	354	505	
	10×16	0.21	0.525	366	523	
82	8×20	0.21	0.525	350	500	
100	8×15	0.34	0.850	308	440	
120	10×16	0.210	0.525	455	650	
	10×20	0.160	0.400	490	700	
150	8×20	0.210	0.525	476	680	
	10×25	0.130	0.325	546	780	
180	10×20	0.160	0.400	553	790	
	10×30	0.100	0.250	672	960	
220	10×25	0.130	0.325	648	925	
	12.5×20	0.110	0.275	609	870	
270	10×30	0.100	0.250	812	1,160	
	12.5×25	0.074	0.185	805	1,150	
330	12.5×20	0.110	0.275	746	1,065	
390	12.5×25	0.074	0.185	1,088	1,280	
	12.5×30	0.068	0.170	1,024	1,360	
470	12.5×30	0.068	0.170	1,120	1,360	
	12.5×35	0.063	0.158	1,112	1,400	
	16×20	0.059	0.148	1,080	1,350	
	16×25	0.055	0.138	1,184	1,480	
560	12.5×40	0.051	0.128	1,224	1,530	
	16×25	0.055	0.138	1,296	1,620	
680	12.5×40	0.051	0.128	1,336	1,670	
	16×31.5	0.046	0.115	1,376	1,720	
820	12.5×40	0.051	0.128	1,480	1,850	
	16×31.5	0.046	0.115	1,512	1,890	
	16×35.5	0.040	0.100	1,528	1,910	
1,000	16×35.5	0.040	0.100	1,576	1,970	
	18×35.5	0.040	0.100	1,688	2,110	
1,500	18×35.5	0.040	0.100	2,169	2,410	

Part Numbering System

RXK Series    470 $\mu\text{F}$      $\pm 20\%$     6.3V    Bulk Package    Gas Type    8 $\phi \times 11.5L$     Pb-free and PET sleeve

**RXK**    **471**    **M**    **0J**    **BK**    -    **0811**

Series Name    Capacitance    Capacitance Tolerance    Rated Voltage    Lead Configuration & Package    Rubber Type    Case Size    Lead Wire and Sleeve type

Note: For more details, please refer to "Part Numbering System (Radial Type)" on page 13.

Radial