

max. 204 m³/h

DC axial fans

Series 4300 119 x 119 x 32 mm




Highlights:

- Ball bearings and sleeve bearings available.
- Optional Vario-Pro: Highly adaptable software configuration of the fan enables a tailor-made solution to the specific requirements of your applications


General characteristics:

- Material: fibreglass-reinforced plastic. Impeller PA, housing PBT.
- Fully integrated electronic commutation.
- Protected against reverse polarity and locking.
- Connection via single strands AWG 22, TR 64. Bared and tin-plated.
- Air exhaust over struts. Direction of rotation clockwise, seen on rotor.
- Mass: 220 g.


Nominal data		Air flow	Air flow	Nominal voltage	Voltage range	Sound pressure level	Sound power level	Sinter sleeve bearings	Ball bearings	Power input	Nominal speed	Temperature range	Service life L ₁₀ (40 °C)	Service life L ₁₀ (T _{max})	Life expectancy L ₁₀ ^Δ	Curve	Specials
Type		m ³ /h	CFM	VDC	VDC	dB(A)	Bel(A)	■ / ■		Watts	RPM	°C	Hours	Hours	Hours		P. 110-116
4312 GL		95	55,9	12	6...15	30	4,3	■		1,2	1 550	-20...+75	80 000 / 35 000	157 500	157 500	1	
4312 L		95	55,9	12	6...15	30	4,3	■		1,2	1 550	-20...+75	80 000 / 35 000	157 500	157 500	1	
4312 GM		140	82,4	12	6...15	39	5,3	■		2,6	2 300	-20...+75	70 000 / 30 000	135 000	135 000	2	
4312 M		140	82,4	12	6...15	39	5,3	■		2,6	2 300	-20...+75	70 000 / 30 000	135 000	135 000	2	/12
4312 G		170	100,1	12	6...15	45	5,8	■		5,0	2 800	-20...+75	62 500 / 27 500	122 500	122 500	3	
4312		170	100,1	12	6...15	45	5,8	■		5,0	2 800	-20...+75	62 500 / 27 500	122 500	122 500	3	/2/19
4312-179		204	120,1	12	6...13,2	51	6,4	■		8,5	3 400	-20...+75	47 500 / 20 000	90 000	90 000	5	
4314 L		95	55,9	24	12...28	30	4,3	■		1,2	1 550	-20...+75	80 000 / 35 000	157 500	157 500	1	
4314 M		140	82,4	24	12...28	39	5,3	■		2,6	2 300	-20...+75	70 000 / 30 000	135 000	135 000	2	
4314 G		170	100,1	24	12...28	45	5,8	■		5,0	2 800	-20...+75	62 500 / 27 500	122 500	122 500	3	
4314		170	100,1	24	12...28	45	5,8	■		5,0	2 800	-20...+75	62 500 / 27 500	112 500	112 500	3	/2/12
4314-147		180	105,9	24	12...28	47	6,1	■		5,8	3 000	-20...+75	57 500 / 25 000	112 500	112 500	4	
4314-180		204	120,1	24	12...26,5	51	6,4	■		9,5	3 400	-20...+75	45 000 / 20 000	90 000	90 000	5	
4318 M		140	82,4	48	36...56	39	5,3	■		3,5	2 300	-20...+75	70 000 / 30 000	135 000	135 000	2	
4318		170	100,1	48	36...53	45	5,8	■		5,0	2 800	-20...+75	62 500 / 27 500	112 500	112 500	3	/2/17



Rotor protrusion max. 0,4 mm.




- Speed-proportional, square-wave signal for external monitoring of the fan motor speed
- 2, 3, or 6 pulses per revolution
- Open-collector signal output
- Extremely wide operating voltage range
- Easy adaptation to user interface
- Connection via separate cable
- The sensor signal also serves as a major comparison variable for setting and maintaining the setpoint speed for interactive or controlled cooling with one or more interconnected fans.




All voltages measured to ground.
External load resistor R_a / U_S / U_{BS} required.

Signal output voltage


Standard signal for all models (exceptions see below)




For multi options control input and 4100 NH7 and NH8



All TD Fans e.g. 6300 TD



Fan speed

Subject to change

Available on request:

- Electrically isolated speed signal circuit
- Varying voltage potentials for power and logic circuit

Signal data	Speed signal U _S Low	Condition: I _{sink}	Speed signal U _S High	Condition: I _{source}	Tach operating voltage U _{BS} max.	Admissible sink current I _{sink} max.	Pulses per revolution	Fan description Basic type
Type	VDC	mA	VDC	mA	VDC	mA		Page
5112 N	≤ 0.4	2	≤ 15	0	5	20	2	66
5114 N / 5118 N	≤ 0.4	2	≤ 60	0	60	20	2	66
5300	≤ 0.4	2	≤ 60	0	60	4	2	67
5300 TD	≤ 0.4	2	≤ 60	0	60	20	6	68
7112 N / 7118 N	≤ 0.4	2	≤ 60	0	60	20	2	69
7114 N	≤ 0.4	2	≤ 30	0	30	20	2	69
7200 N	≤ 0.4	2	≤ 15	0	15	20	2	70
6400	≤ 0.4	2	≤ 60	0	60	20	2	71
6300 TD	≤ 0.4	2	≤ 60	0	60	20	6	75
6300 N	≤ 0.4	2	≤ 60	0	60	20	6	76
6300 NTD	≤ 0.4	2	≤ 60	0	60	20	6	77
6300	≤ 0.4	2	≤ 60	0	60	20	2	78
DV 6300 TD	≤ 0.4	2	≤ 60	0	60	20	6	80
2200 FTD	≤ 0.4	2	≤ 60	0	60	20	6	81
RL 48	≤ 0.4	2	≤ 30	0	30	4	2	97
RL 65	≤ 0.4	2	≤ 30	0	30	4	2	98
RL 90 N	≤ 0.4	2	≤ 30	0	30	4	2	99
RLF 100	≤ 0.4	2	≤ 30	0	30	4	2	100
RG 90 N	≤ 0.4	2	≤ 30	0	30	4	2	101
RG 125 N	≤ 0.4	2	≤ 30	0	30	4	2	102
RG 140 N	≤ 0.4	3	≤ 60	0	60	4	2	103
RG 160 N	≤ 0.4	2	≤ 30	0	30	20	2	104
RG 160 NTD	≤ 0.4	2	≤ 60	0	60	20	6	105
RG 190 TD	≤ 0.4	2	≤ 60	0	60	20	6	106
RG 220 TD	≤ 0.4	2	≤ 60	0	60	20	6	107
RG 225 TD	≤ 0.4	2	≤ 60	0	60	20	6	108
RET 97 TD	≤ 0.4	2	≤ 60	0	60	20	6	109
REF 100	≤ 0.4	2	≤ 30	0	30	4	2	110
RER 120 TD	≤ 0.4	2	≤ 60	0	60	20	6	112
RER 133 TD	≤ 0.4	2	≤ 60	0	60	20	6	117
RER 160 NTD	≤ 0.4	2	≤ 60	0	60	20	6	119
REF 175 TD	≤ 0.4	2	≤ 60	0	60	20	6	120
RER 175 TD	≤ 0.4	2	≤ 60	0	60	20	6	121
RER 190 TD	≤ 0.4	2	≤ 60	0	60	20	6	122
RER 220 TD	≤ 0.4	2	≤ 60	0	60	20	6	128
RER 225 TD	≤ 0.4	2	≤ 60	0	60	20	6	129
Subject to change								

Note:

Fans that come with these fan specials could have variations with respect to the temperature range, voltage range, and power consumption compared to standard fans without specials.