

8 7 6 5 4 3 2 1

NOTES:

1. MOUNTING: Panel mounting hole .171" (4.34mm) Diameter
 Litepipe from .200" to .500" use grommet retainer RTN 150
 Litepipe from .500" to 2.00" the spring retainer RTN 250 is recommended for rigidity
2. Standoff used to adjust the height of a standard LED above the PCB to maintain a maximum .050" clearance between Litepipe and LED.
3. U.S. & Foreign Pat Issued & Pend.

REVISIONS				
ECN #	REV	DESCRIPTION	DATE	INITIALS
	N/A	INITIAL RELEASE	8/25/98	JS
	1	UPDATE DWG FORMAT	12/15/08	JG
	2	REVISE .170" DIMENSION TOLERANCES	3/11/09	AZ
	001	REVISED PER ECR111009AZ01	4/23/10	KH

**RETAINERS
(ORDER SEPARATELY)**




SECTION A-A



ORDERING CODE: **LPC XXX CTP**

LENGTH CODE (Min 020=.200" / Max 200=2.000")											
020	038	056	074	092	112	135	157	180			
022	040	058	076	094	115	137	160	182			
024	042	060	078	096	117	140	162	185			
026	044	062	080	098	120	142	165	187			
028	046	064	082	100	122	145	167	190			
030	048	066	084	102	125	147	170	192			
032	050	068	086	105	127	150	172	195			
034	052	070	088	107	130	152	175	197			
036	054	072	090	110	132	155	177	200			
SPECIAL LENGTHS UPON REQUESTS											

COLOR	
CTP	CLEAR



UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES		MATERIAL		VISUAL COMMUNICATIONS COMPANY, INC.	
ANGLES	DECIMALS	ACRYLIC (OPTICAL GRADE)		190 Bossick Boulevard, Suite 101 San Marcos, CA 92069 USA	
±1"	.X ±.020	UL 94-HB		Phone (760) 560-1300 Fax (760) 560-1301 email vccsales@vccite.com	
FINISH	.XX ±.010	FINISH		TITLE:	
	.XXX ±.005	SEE NOTES		CLIPLITE 4MM LITEPIPE	
THIRD ANGLE PROJECTION		APPROVAL		DATE	
DRAWN		K.Howard		4/23/10	
CHECKED		DPZ		5/4/10	
DO NOT SCALE DRAWING		SIZE		DWG. NO.	
		B		LPC XXX CTP	
		SCALE: 8:1		REV	
		SHEET 1 OF 1		001	

8 7 6 5 4 3 2 1