



D-SUBMINIATURE CONNECTORS:
K202XHT Series
 Right Angle Surface Mount

K202XHT Series Dimensions
 Dimensions in mm



| Shell Size | In mm | | | | |
|------------|----------------|----------------|----------------|----------------|----------------|
| | A | A1 | B | C | D |
| 9 (E) | ±.010 ±0.25 | ±.010 ±0.25 | ±.005 ±0.13 | ±.015 ±0.38 | ±.005 ±0.13 |
| 15 (E) | .643 16.33 | N/A | .984 24.99 | 1.213 30.81 | .609 15.46 |
| 25 (B) | 1.511 38.38 | 1.534 38.96 | 1.852 47.04 | 2.088 53.04 | 1.498 38.06 |

A = Exterior of Female Shell (S)
 A1 = Interior of Male Shell (P)

| | | | |
|-----------------------|---------------------|----------------------|------------------|
| 2D Drawing | IGES | STEP | 3D PDF |
| Solder Profile | CofC RoHS Compliant | CofC REACH Compliant | UL Plastic File |
| Certificate of Origin | Check Stock | Request a Sample | Send Us An Email |

Generated Part Number

Part Number Builder

-
 Series Shell Size Contact Contact Type Mounting Option Plating Option

Series

K202XHT - D-Subminiature Connector, Right Angle, Ultra Short Footprint, Surface Mount, Reflow Compatible

Shell Size-Contact Option

- E - 9 Contacts
- B - 25 Contacts
- E - 15 Contacts, High Density (Socket only)

Contact Type

- P - Pin Contact (Plug)
- S - Socket Contact (Receptacle)

Mounting Option

- N - With Boardlocks and #4-40 UNC Threaded Inserts
- NJ - With Boardlocks and JSX-1055 Jackscrews Installed

Plating Option

- Blank - Gold Flash
- 15 - 15µ" Gold
- 30 - 30µ" Gold

Contact Kycon for Tape and Reel and Other Options