

HIGHLIGHTS


FEATURES

- Spring Clamp Technology
- **CXVF**: Accepts 5x20, 5x25 or 6.3x32mm Fuse types
- **CXVF2.5**: Accepts 5x20, 5x25 or 6.3x32mm Fuse types, 1 Input – 2 Outputs
- **CXAF4/3**: Accepts Automotive ATO Fuse


APPLICATIONS

- Control systems with Fuse Protection
- Disconnect Applications


CXVF



CXVF2.5



CXAF4/3



Dimensions

	Fuse Block 5x20mm, 5x25mm, 1/4x11/4"	Fuse Block, 1 In - 2 Out 5x20mm, 5x25mm, 1/4x11/4"	Fuse Block, ATO Fuse 3 Connections
Width	12 mm	12 mm	6 mm
Length	75.0 mm	75.0 mm	86.2 mm
Height w DIN Rail	35 x 7.5 mm 35 x 15 mm	43.0 mm 50.5 mm	43.2 mm 50.7 mm
Weight per piece	30.0 g	30.0 g	13.1 g

Technical Data/Ratings

Approvals						
Wire Size (solid stranded)	24-8 AWG 0.2-10 mm ²		24-8 AWG 0.2-10 mm ²		24-10 AWG 0.2-4 mm ²	
Voltage Rating	600 V 1000V AC/DC		600 V 1000V AC/DC		600 V 1000V AC/DC	
Current Rating	10 A		10 A		10 A	
Insulation Material	Polyamide 66		Polyamide 66		Polyamide 66	

Fuse Specifications

Fuse Type	5x20, 5x25, 6.3x32 mm	5x20, 5x25, 6.3x32 mm	ATO, 19.1x5.1x18.5 mm
-----------	-----------------------	-----------------------	-----------------------

Installation Instructions

Wire Stripping Length	10 mm	10 mm	10 mm
Screwdriver	Flat Head 0.6 x 3.5 mm	Flat Head 0.6 x 3.5 mm	Flat Head 0.6 x 3.5 mm

Terminal Blocks

	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.
Fuse Types						
5 x 20 mm	CXVFA	50	CXVF2.5A	50	—	—
5 x 25 mm	CXVFB	50	CXVF2.5B	50	—	—
6.3 x 32 mm	CXVFC	50	CXVF2.5C	50	—	—
Automotive	—	—	—	—	CXAF4/3	50

Accessories

Accessories		Cat. No.	Std. Pk.	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.
DIN Rail		2511120 CA701-15/S	20 10	2511120 CA701-15/S	20 10	2511120 CA701-15/S	20 10
Endplate		—	—	—	—	EPCX4/4	50
End Stop		CA103 CA702 CA802	50 50 50	CA103 CA702 CA802	50 50 50	CA103 CA702 CA802	50 50 50
Shorting Link/ Jumpers		JX4/2	100	JX4/2	100	JX4/2	100
		JX4/3	50	JX4/3	50	JX4/3	50
		JX4/4	50	JX4/4	50	JX4/4	50
		JX4/8	50	JX4/8	50	JX4/8	50
		JX4/10	10	JX4/10	10	JX4/10	10
		JX4/16	10	JX4/16	10	JX4/16	10
Marking Tag		MT12	1Pk (100 tags)	MT12	1Pk (100 tags)	MT6	1Pk (100 tags)