




Electrical Characteristics

Nominal Impedance: 50 ohms
Frequency Range: DC to 4 GHz
Power: 0.5 Watts
Operating Voltage (rms): 500 V maximum at sea level
Dielectric Withstand Voltage (rms): 1500 V maximum at sea level
Contact Resistance: 1.5 milliohms maximum

Mechanical Characteristics

Mating Cycles: 500 cycles minimum
Interface Dimensions: Conform to MIL-C-39012

Environmental Characteristics

Temperature Range: -55 °C to +85 °C

	PART	DESCRIPTION
1	Body	Brass, nickel plated 1.78µm minimum
2	Resistor	50 Ohm 1/2 Watt
3	Contact	Brass, gold plated 0.076µm - 0.127µm
4	Dielectric	POM
5	Shell	Zink, nickel plated 1.78µm minimum

CAD Issue	PDC	1	14 Oct 02
First Issue	CN	A	09 Feb 95
DESCRIPTION OF REVISION	APPVD	ISS	DATE



Cinch Connectivity Solutions
7-13 Russel Way,
Widford Industrial Estate,
Chelmsford, Essex,
CM1 3AA, UK.
Tel: +44 (0) 1245 359515
Fax: +44 (0) 1245 358938

SCALE: Not To Scale	DRAWN BY:	P D Couzens
DIMENSIONS: mm	CHECKED BY:	S Nash
TOLERANCES: ± 0.2mm unless otherwise stated	APPROVED BY:	A J Tatner
	DATE:	14 Oct 02

TITLE:	PART NUMBER:
BNC 50 Ohm Terminator 1/2 W	VBT50
	PAGE: 1 of 1