





Recommended Panel Cutout









Notes:

1. Material and Finish:
   - Receptacle Housing, Protective Cover: Polyester (Black); UL94 V-0
   - Panel Nut: Brass, Finish: Nickel Plated
   - Panel Gasket: Silicon, Color: White
   - Cover Gasket: Silicon, Color: White
   - Tether: Polycarbonate, Color: Black

   Duplex LC Adaptor Assembly:
   - Housing: Mod. PPO , UL94 V-0,
     Color: **SM Blue/MM Beige/APC SM Green**
   - Alignment Sleeves: SM Ceramic/MM Phosphor Bronze
   - Dust Cap: PP, Color: Neutral transparent
   - Operating Temperature: -40~C to +85~C
2. Connector can be front or rear mounted to a maximum panel thickness of 3.2mm.
3. IP67 rated when covered or fully mated with the appropriate mating connector

Directive 2002/95/EC RoHS Compliant

Description	Part Number
Plastic Duplex LC Single Mode Receptacle Assembly + Cover Assembly	17-300230
Plastic Duplex LC Multi Mode Receptacle Assembly + Cover Assembly	17-300240
Plastic Duplex LC APC Single Mode Receptacle Assembly + Cover Assembly	17-300250

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, NOR MAY IT BE DISCLOSED TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC CORPORATION.

DO NOT ALTER CAD DRAWING BY HAND

Customer:

Name	Title	Approval Date

Rev.	Changes	Date	Name
a	original		

Tolerance
Unless otherwise specified
0 PLC ± 0.30
1 PLC ± 0.20
2 PLC ± 0.10
3 PLC ± 0.05
ANGLES ± 1°

Autodesk Inventor

2011	Date	Name
Draw.	Mar. 04	Vincent Ke
Appd.	Mar. 04	J. Chaudry
Norm		
D-old		

CONEC®

Scale: 1.5:1

Dim. in mm

Material: See Notes

Title: IP67 Industrial Duplex LC Receptacle Assembly + Cover Assembly
Plastic version

Drawing No.: 17K1A217

DIN A3

Part No.: SEE ABOVE TABLE

Sheet 1/1