


# Power Transformers Fully Enclosed 4801 - 4807





LOW VOLTAGE RECTIFIER Transformers with fully enclosed vertical end covers.

- Primary voltage, 115 Volts, 60 Hz.
- Primary and secondary leads 8-10" long.
- 4-hole vertical mounting.
- 7 sizes are available, covering the range: 30 to 100 VA.
- CSA listed (LR 47366).



## MECHANICAL



Dimensions, Inches

P/N	DIMENSIONS			
	L	W	H	D E F G
4801	2.50	2.13	3.00	2.00 1.19 0.375 0.190
4802	2.50	2.38	3.00	2.00 1.44 0.375 0.190
4803	2.50	2.63	3.00	2.00 1.68 0.375 0.190
4804	2.50	2.88	3.00	2.00 1.94 0.375 0.190
4805	2.50	3.13	3.00	2.00 2.19 0.375 0.190
4806	2.50	3.38	3.00	2.00 2.44 0.375 0.190
4807	2.50	3.63	3.00	2.00 2.69 0.375 0.190

## ELECTRICAL SPECIFICATION

Part No.	Secondary Voltages (A-A)		
	F.L. Volts	N.L. Volts	Current Amps
4801-01	5.0	5.40	3.00
4802-01	5.0	5.43	6.00
4802-02	6.3	6.90	4.00
4802-03	12.6	13.80	2.00
4802-04	25.0	27.50	1.00
4802-05	28.0	30.80	1.00
4802-06	36.0	39.50	1.00
4802-07	50.0	51.80	5.00
4802-08	60.0	65.20	0.50
4803-01	5.0	5.35	8.00
4803-02	6.3	6.70	6.00
4803-03	10.0	10.70	4.00
4803-04	16.0	17.40	3.00
4803-05	18.0	19.40	3.00
4803-06	25.0	26.80	1.50
4803-07	33.0	35.00	1.00
4803-08	50.0	54.50	1.00
4803-09	80.0	85.50	0.50
4803-10	100.0	107.00	0.50
4804-01	5.0	5.35	10.00
4804-02	6.3	6.74	8.00
4804-03	10.0	10.70	5.00
4804-04	10.0	10.70	5.00
4804-05	11.0	11.80	5.00
4804-06	12.6	13.40	4.00
4804-07	14.0	15.10	4.00

Part No.	Secondary Voltages (A-A)		
	F.L. Volts	N.L. Volts	Current Amps
4804-08	24.0	25.60	2.00
4804-09	28.0	29.80	2.00
4804-10	30.0	31.60	1.50
4805-01	6.3	6.70	10.00
4805-02	20.0	20.80	3.00
4805-03	36.0	38.30	2.00
4805-04	60.0	63.50	1.00
4805-05	120.0	127.00	0.50
4806-01	5.0	5.30	15.00
4806-02	6.3	6.80	12.00
4806-03	10.0	10.60	8.00
4806-04	12.6	13.60	6.00
4806-05	25.0	26.80	3.00
4806-06	28.0	29.60	3.00
4807-01	5.0	5.30	20.00
4807-02	10.0	10.70	10.00
4807-03	12.6	13.30	8.00
4807-04	14.0	15.10	6.00
4807-05	16.0	17.40	5.00
4807-06	18.0	18.70	5.00
4807-07	25.0	26.60	4.00
4807-08	30.0	32.00	3.00
4807-09	44.0	46.00	2.00
4807-10	50.0	53.20	2.00
4807-11	80.0	85.20	0.50
4807-12	100.0	106.50	1.00

ISSUE: C 4801\_CHP 9/50/712