

## METRIC MEASUREMENT VERSION

## 77005W Multi-Conductor - 600V Unshielded, Continuous Flexing Applications Up to 14 Million Flex Life Cycles



For more Information  
please call

1-800-Belden1

**General Description:**

20 AWG stranded (63x38) bare copper conductors, PVC insulation, oil-resistant overall PVC jacket.

**Physical Characteristics (Overall)****Conductor**

AWG:

# Conductors	AWG	Stranding	Conductor Material	Dia. (mm)
4	20	63x38	BC - Bare Copper	1.016

Total Number of Conductors: 5

**Ground Wire**

Ground Wire (Y/N):	Y
Ground Wire AWG:	20
Ground Wire Stranding:	63x38
Ground Wire Conductor Material:	BC - Bare Copper
Ground Wire Insulation Material:	PVC - Polyvinyl Chloride

**Insulation**

Insulation Material:

Insulation Material	Wall Thickness (mm)	Dia. (mm)
PVC - Polyvinyl Chloride	0.559	2.134

Insulation Color Code Chart:

Color	Description
Red	Individually Numbered
Yellow/Green	Ground

**Outer Shield**

Outer Shield Separator Material: Tissue Tape, 25x37; Overlap, Min.

**Outer Jacket**

Outer Jacket Material:

Outer Jacket Material	Nom. Wall Thickness (mm)
PVC - Polyvinyl Chloride	0.889

**Overall Cable**

Overall Nominal Diameter: 8.204 mm

**Mechanical Characteristics (Overall)**

Storage Temperature Range:	-40°C To +90°C
Installation Temperature Range:	Flexing: -5°C To +90°C
Operating Temperature Range:	Flexing: -5°C To +90°C
Bulk Cable Weight:	238.112 Kg/Km
Max. Recommended Pulling Tension:	177.928 N
Min. Bend Radius/Minor Axis:	66.040 mm
Min. Bend/Installation:	66.040 mm
Min. Bend Radius (Continuous Flexing):	66.040 mm
Flex Cycle Rating:	14 Million Flexes

**Applicable Specifications and Agency Compliance (Overall)****Applicable Standards & Environmental Programs**

NEC/(UL) Specification:	THHN/THWN Singles
AWM Specification:	UL Style 2587 (600 V 90°C)
CSA Specification:	600 V AWM I/II A/B
EU Directive 2011/65/EU (ROHS II):	Yes
Other Specification:	AWM/STYLE 10012, AWM/STYLE 2587, AWM I/II A/B, FT1, VDE 0472, Section 803 Oil Test, EU Low Voltage Directive 2014/35/EC, EU Directive 2011/65/EU (RoHS2), REACH Regulation (EC 1907/2006), California Proposition 65

METRIC MEASUREMENT VERSION

77005W Multi-Conductor - 600V Unshielded, Continuous Flexing Applications Up to 14 Million Flex Life Cycles

Flame Test

CSA Flame Test: FT1

Electrical Characteristics (Overall)

Nom. Inductance:

Inductance (µH/m)
0.656

Nom. Capacitance Cond. to Other Cond. & Ground:

Description	Freq. (kHz)	Capacitance (pF/m)
Nom. Cond. to Cond	1.000	91.868

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/km)
35.763

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
--------	-------	-------------	-------	-------	-----------

Revision Number: 0      Revision Date: 09-27-2017

© 2017 Belden, Inc.  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale.