9001SKY105



Device short name	SKY	
Enclosure type Weatherproof enclosure dust and oil resistant indoor/outdoor Enclosure corrosion resistance indoor/outdoor		
Mounting diameter	1.18 in (30 mm)	
Provided equipment	Contact block 1 KA3 Legend plate 1 KN102RP	

Complementary

Line Rated Current	10 A
Contacts type and composition	1 NC
Control type	Push-button 1 9001SKR3R
Device mounting	Surface
Electrical connection	Screw clamp terminal
Enclosure material	Polymeric
Marking	STOP
Operator profile	1 projecting push-button
Permissible voltage	<= 600 V

Environment

NEMA degree of protection	NEMA 3/4/4X/13	
product certifications	CE	-
	CSA LR25490 class 3211 03	
	UL listed file E42259 CCN NKCR	

Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 1002 - Schneider Electric declaration of conformity	Compliant - since 1002 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Need no specific recycling operations	Need no specific recycling operations
WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:
Nickel compounds, which is known to the State of California to cause cancer, and	Nickel compounds, which is known to the State of California to cause cancer, and
Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm.	eDi-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm.
For more information go to www.p65warnings.ca.gov	For more information go to www.p65warnings.ca.gov

Contractual warranty

Warranty period	18 months
Warranty period	10 months