



CUSTOMER TERMINAL	RoHS	LEAD(Pb)-FREE
Sn96%, Ag4%	Yes	Yes

more than you expect



ELECTRICAL SPECIFICATIONS @ 25°C unless otherwise noted:

PARAMETER	TEST CONDITIONS	VALUE
D.C. RESISTANCE	1-3 @20°C	0.159 ohms ±10%
D.C. RESISTANCE	4-6 @20°C	1.03 ohms ±10%
INDUCTANCE	4-6 10kHz, 100mVAC, Ls	239uH ±8%
DIELECTRIC	3-4 500VAC, 1 second	500VAC, 1 minute
TURNS RATIO	(4-6):(3-1)	4.5:1, ±1%
TURNS RATIO	(4-6):(2-1)	9:1, ±1%

GENERAL SPECIFICATIONS:

OPERATING TEMPERATURE RANGE: -40°C to +125°C including temp rise.

Safety standard undefined.

Wire insulation & RoHS status not affected by wire color.
Wire insulation color may vary depending on availability.

REV.	DATE	Packaging Specifications
		Method: Tape & Reel
		PKG-0637
		www.we-online.com/midcom
6B	2/18	
6A	9/17	SEE REVISION SHEET FOR REVISION LEVEL



Tolerances unless otherwise specified:
Angles: ±1°
Fractions: ±1/64
Decimals: ±.005 [.13]
Footprint: ±.005 [.13]

This drawing is dual dimensioned. Dimensions in brackets are in millimeters.

DRAWING TITLE
TRANSFORMER

eiSos p/n: 750316928



PART NO.
750316928

SPECIFICATION SHEET 1 OF 1