



Main

Range of product	9007
Series name	Heavy duty
Device short name	C
Head type	Turret head rotary lever
Type of operator	Spring return lever arm (first stage : 10° - second stage : 2.5°) (to be ordered separately) Spring return lever arm (standard pre-travel)
Switch actuation	CCW
Cable entry	NPT conduit entry, cable outer diameter: 0.5 in
Contacts type and composition	2 NO/2 NC
Contact operation	Snap action Two stage

Complementary

Body material	Zinc alloy
Switch function	SPDT-DB
Contact form	Form ZZ
Contacts material	Silver alloy (Ag/Ni)
Minimum torque for tripping	4 lbf.in
Tripping angle	4 °
Maximum displacement angle	90 °
[Ie] rated operational current	10 A, A600 10 A, R300
[Ui] rated insulation voltage	<= 600 V
Product certifications	CE CSA UL listed
Provided equipment	Receptacle

Environment

ambient air temperature for operation	-20...185 °F
---------------------------------------	--------------

Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 1150 - Schneider Electric declaration of conformity	Compliant - since 1150 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Need no specific recycling operations	Need no specific recycling operations
WARNING: This product can expose you to chemicals including:	WARNING: This product can expose you to chemicals including:
Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and	Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and
Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm.	Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm.
For more information go to www.p65warnings.ca.gov	For more information go to www.p65warnings.ca.gov

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Contractual warranty

Warranty period

18 months