

## **SPECIFICATION FOR APPROVAL**

Customer		
Description	DC FAN	
Part No.		Rev
Delta Model No.	AFB0624EH-TA50	Rev. <u>00</u>
Sample Issue No.		
Sample Issue Date.	Aug 20, 09	

BACK AFTER YOU	E COPY OF THIS SPECIFICATION SIGNED APPROVAL FOR PRODUC-
TION PRE-ARRANGE	MENT.
APPROVED BY	:
DATE	:

## **DELTA ELECTRONICS (THAILAND) PUBLIC COMPANY LIMITED.**

111 MOO 9 WELLGROW INDUSTRIAL ESTATÉ BANGNA-TRAD ROAD, TAMBON BANGWUA, AMPHUR BANGPAKONG, CHACHOENGSAO 24180 THAILAND TEL. +66-(0)-38522455, FAX. +66-(0)-38522477 DELTA ELECTRONICS (THAILAND) PCL.

111 MOO 9, WELLGROW INDUSTRIAL ESTATE, BANGNA-TRAD ROAD, BANGWUA, BANGPAKONG, FAX: +66-(0)38-522455

CHACHEONGSAO 24180 THAILAND.

# 

Cu	${ m sto}$	$\mathbf{m}$	er	:

Description:	DC_FAN		
Customer P/N:		REV:	
Delta Model NO.:	AFB0624EH-TA50		
Sample Rev:	00	Issue N0:	
Sample Issue Date:	Δ11σ 20 09	Quantity:	

#### 1. SCOPE:

THIS SPECIFICATION DEFINES THE ELECTRICAL AND MECHANICAL CHARACTERISTICS OF THE DC BRUSHLESS AXIAL FLOW FAN. THE FAN MOTOR IS WITH TWO PHASES AND FOUR POLES.

#### 2. CHARACTERS:


ITEM	DESCRIPTION
RATED VOLTAGE	24 VDC
OPERATION VOLTAGE	14.0 - 27.6 VDC
INPUT CURRENT	0.24 (MAX. 0.36) A
INPUT POWER	5.76 (MAX. 8.64) W
SPEED	6800±10% R.P.M.
MAX. AIR FLOW (AT ZERO STATIC PRESSURE)	1.086 (MIN. 0.977 ) M $^3/$ MIN. 38.35 (MIN. 34.50 ) CFM
MAX. AIR PRESSURE (AT ZERO AIRFLOW)	$\begin{array}{c} 13.81 \; (\text{MIN.} \; 11.18 \; ) \; \; \text{mmH}_2\text{O} \\ 0.544 \; (\text{MIN.} \; 0.441 \; ) \; \; \text{inchH}_2\text{O} \end{array}$
ACOUSTICAL NOISE (AVG.)	46.5 (MAX. 50.5) dB-A
INSULATION TYPE	UL: CLASS A

(continued)

PART NO:	
DELTA MODEL:	AFB0624EH-TA50

INSULATION STRENGTH	10 MEG OHM MIN. AT 500 VDC (BETWEEN FRAME AND (+) TERMINAL)
DIELECTRIC STRENGTH	5 mA MAX. AT 500 VAC 60 Hz ONE MINUTE, (BETWEEN FRAME AND (+) TERMINAL)
EXTERNAL COVER	OPEN TYPE
LIFE EXPECTANCE	70,000 HOURS CONTINUOUS OPERATION AT 40 °C WITH 15 ~ 65 %RH.
ROTATION	CLOCKWISE VIEW FROM NAME PLATE SIDE
OVER CURRENT SHUT DOWN	THE CURRENT WILL SHUT DOWN WHEN LOCKING ROTOR
LEAD WIRE	UL 1007 -F- AWG #24 BLACK WIRE NEGATIVE(-) RED WIRE POSITIVE(+)

- NOTES: 1. ALL READINGS ARE MEASURED AFTER STABLY WARMING UP THROUGH 10 MINUTES.
  - 2. THE VALUES WRITTEN IN PARENS, ( ), ARE LIMITED SPEC.
  - 3. ACOUSTICAL NOISE MEASURING CONDITION:



NOISE IS MEASURED AT RATED VOLTAGE IN FREE AIR IN ANECHOIC CHAMBER WITH B & K SOUND LEVEL METER WITH MICROPHONE AT A DISTANCE OF ONE METER FROM THE FAN INTAKE.

PART NO:	
DELTA MODEL: AFB0624EH-TA50	
3. MECHANICAL:	
3-1. DIMENSIONS	SEE DIMENSIONS DRAWING
3-2. FRAME	PLASTIC UL: 94V-0
3-3. IMPELLER	PLASTIC UL: 94V-0
3-4. BEARING SYSTEM	TWO BALL BEARINGS
3-5. WEIGHT	80 GRAMS
3-6. INGRESS PROTECTION	IP55
4. ENVIRONMENTAL:	
4-1. OPERATING TEMPERATURE	10 TO +70 DEGREE C
4-2. STORAGE TEMPERATURE	40 TO +75 DEGREE C
4-3. OPERATING HUMIDITY	5 TO 90 % RH
4-4. STORAGE HUMIDITY	5 TO 95 % RH
5. PROTECTION:	
5-1. LOCKED ROTOR PROTECTION	
IMPEDANCE OF MOTOR WINDING PROT HOURS OF LOCKED ROTOR CONDITION	
5-2. POLARITY PROTECTION	
BE CAPABLE OF WITHSTANDING IF REAND NEGATIVE LEADS.	VERSE CONNECTION FOR POSITIVE
6 DE OZONE DEDIEMING GUDGMANGEG	

- 6. RE OZONE DEPLETING SUBSTANCES:
  - 6-1. NO CONTAINING PBBs, PBB0s, CFCs, PBBEs, PBDPEs AND HCFCs.
- 7. PRODUCTION LOCATION
  - 7-1. PRODUCTS WILL BE PRODUCED IN CHINA OR THAILAND.

PART NO:
TAKT NO.

DELTA MODEL: AFB0624EH-TA50

#### 8. BASIC RELIABILITY REQUIREMENT:

8-1. THERMAL LOW TEMPERATURE: -40°C HIGH TEMPERATURE: +80°C SOAK TIME: 30 MINUTES

TRANSITION TIME < 5 MINUTES

DUTY CYCLES: 5

8-2. HUMIDITY TEMPERATURE:  $+25^{\circ}\text{C} \sim +65^{\circ}\text{C}$  EXPOSURE HUMIDITY: 90-98% RH @  $+65^{\circ}\text{C}$ 

FOR 4 HOURS/CYCLE

POWER: NON-OPERATING TEST TIME: 168 HOURS

8-3. VIBRATION TEMPERATURE: +25°C

ORIENTATION: X, Y, Z POWER: NON-OPERATING

VIBRATION LEVEL: OVERALL gRMS=3.2

FREQUENCY(Hz)	PSD(G^2/Hz)
10	0.040
20	0.100
40	0.100
800	0.002
1000	0.002

TEST TIME: 2 HOURS ON EACH ORIENTATION

8-4. MECHANICAL TEMPERATURE: +20°C SHOCK ORIENTATION: X, Y, Z

POWER: NON-OPERATING ACCELERATION: 20 G MIN.

PULSE: 11 ms HALF-SINE WAVE NUMBER OF SHOCKS: 5 SHOCKS

FOR EACH DIRECTION

8-5. LIFE TEMPERATURE: MAX, OPERATING TEMPERATURE

POWER: OPERATING


DURATION: 1000 HOURS MIN.

D.D. N.O.

PART NO:

DELTA MODEL: AFB0624EH-TA50

## 9. P & Q CURVE:



\* TEST CONDITION: INPUT VOLTAGE ---- OPERATION VOLTAGE TEMPERATURE ---- ROOM TEMPERATURE HUMIDITY ----- 65%RH

page: 5

-----


PART NO:

DELTA MODEL: AFB0624EH-TA50

\_\_\_\_\_\_

#### 10. DIMENSION DRAWING:





#### NOTES:

- 1. WIRE: UL1007 AWG#24 BLACK WIRE ---(-) RED WIRE ----(+)
- 2. FOR IP55 PROTECTION, THE MOTOR(PWB+WINDING ASSY) MUST COATED BY PARYLENE WITH THICKNESS 0.005mm. (REF.) DELTA P/N 4020158300
- 3. THIS PRODUCT IS ROHS COMPLIANT

page: 6 A00



### **Descriptions:**

- 1. Delta will not guarantee the performance of the products if the application condition falls outside the parameters set forth in the specification.
- A written request should be submitted to Delta prior to approval if deviation from this specification is required.
- 3. Please exercise caution when handling fans. Damage may be caused when pressure is applied to the impeller, if the fans are handled by the lead wires, or if the fans are hard-dropped to the production floor.
- 4. Except as pertains to some special designs, there is no guarantee that the products will be free from any such safety problems or failures as caused by the introduction of powder, droplets of water or encroachment of insect into the hub.
- 5. The above-mentioned conditions are representative of some unique examples and viewed as the first point of reference prior to all other information.
- 6. It is very important to establish the correct polarity before connecting the fan to the power source. Positive (+) and Negative (-). Damage may be caused to the fans if connection is with reverse polarity, as there is no foolproof method to protect against such error.
- 7. Delta fans are not suitable where any corrosive fluids are introduced to their environment.
- 8. Please ensure all fans are stored according to the storage temperature limits specified. Do not store fans in a high humidity environment. We highly recommend performance testing is conducted before shipping, if the fans have been stored over 6 months.
- 9. Not all fans are provided with the Lock Rotor Protection feature. If you impair the rotation of the impeller for the fans that do not have this function, the performance of those fans will lead to failure.
- 10. Please be cautious when mounting the fan. Incorrect mounting of fans may cause excess resonance, vibration and subsequent noise.
- 11. It is important to consider safety when testing the fans. A suitable fan guard should be fitted to the fan to guard against any potential for personal injury.
- 12. Except where specifically stated, all tests are carried out at relative (ambient) temperature and humidity conditions of 25°C, 65%. The test value is only for fan performance itself.
- 13. Be certain to connect an "over 4.7μF" capacitor to the fan externally when the application calls for using multiple fans in parallel, to avoid any unstable power.