




B

NOTES:

1. MAXIMUM CONNECTOR INSERTION LOSS (IL): 0.5dB,
PLUS CABLE ATTENUATION OF 3.5dB/km AT 850nm

- ## 2. TEST DATA PROVIDED WITH EACH ASSEMBLY



FIBER PATH DETAIL

Directive 2002/95/EC RoHS Compliant

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. CONECS CORPORATION OWNERSHIP AND COPYRIGHT © OF CONEC CORPORATION DRAWING NOT ALTER CAD DRAWING BY HAND	Customer:				Tolerance Unless otherwise specified			Scale: NTS		Dim. in m [inches]	
	Name		Title	Approval Date			Autodesk Inventor	Material:			
					2011	Date	Name	Title: IP67 Industrial Duplex LC (ODVA)			
					Draw.	Apr. 21	Vincent Ke	MM Fiber Optic Patch Cords (50/125um)			
					Appd.	Apr. 21	J. Chaudry	Nickel Plated Zinc Die-Cast Version			
					Norm						
					D-old						
	a	original						Drawing No.: 17K1A228		DIN A3	
	Rev.	Changes	Date	Name				Part No.: SEE TABLE		Sheet 1/1	



A

1