## RAFIX 22 FS<sup>+</sup> - Mushroom-headed pushbutton, momentary, illuminated 1.30.276.201/2200



 $\langle \rangle$ 

General information	
Form of lens	conical mushroom form
Color of lens	black
Form of collar	round
Dimensions	
Mushroom Diameter	<u>30 mm</u>
Overall height	33.2 mm
Mounting depth	PCB 9.2 mm, QC 27 mm
Mounting hole	_22.3 mm
Diameter of collar	29.8 mm
Mechanical design	
	ring nut
Mounting Contact function	
	momentary
Illuminability	yes
Reset	
Torque for nut ring	<u>1.2 Nm</u>
Mechanical characteristics	
Robustness max.	100 N
Other specifications	
Ambient temp. operating min.	-25 °C
Ambient temp. operating max.	+70 °C
Storage temperature min.	-40 °C
Storage temperature max.	+80 °C
Operating life	50,000 cycle
B10	65,000 cycle
Degree of protection from front side	IP65 (DIN EN 60529)
Environmental restistance	acc. to IEC 60068-2-14, -30, -33 and -78
Salt spray	IEC 600 68-2-11
Robustness	acc. to IEC 600 68-2-3 und 2-30
ROHS compliant	yes
REACH compliant	yes



## Panel cut-out to IEC 60947-5-1



